


MW-5

2011079

WATER WELL RECORD

Form WWC-5

KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Barton Barton		NW 1/4 NE 1/4 NE 1/4	32	T 19 S	R 14 EW
Distance and direction from nearest town or city street address of well if located within city? 2823 10th Street 13					
2 WATER WELL OWNER: RR#, St. Address, Box # : Klepper Oil Co. City, State, ZIP Code : 2617 N Broadway, Wichita KS 67219 Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 14.5 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1 9.15 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 9.15 ft. below land surface measured on mo/day/yr 3-18-93 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter in. to ft. Dia in. to ft. Dia in. to ft. Casing height above land surface Flush in. weight 703 lbs./ft. Wall thickness or gauge No. 15 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 4.5 ft. to 14.5 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 3.5 ft. to 14.5 ft. From ft. to ft.					
6 GROUT MATERIAL: Grout Intervals: From 3.5 ft. to 1 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? NE How many feet? 280					
LITHOLOGIC LOG					
FROM	TO	LITHOLOGIC LOG		FROM	TO
0.0	4.5	Silt, Sandy, Clayey			
4.5	7.0	Silt, Clayey			
7.0	9.0	Sand, very coarse			
9.0	12.0	Clay, silty			
12.0	14.0	Sand, very coarse			
14.0	14.5	Clay, silty			
Flush mount waiver granted 1-27-93 for Klepper Oil Co.; KDHE 06005661 by Don Taylor					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-18-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 3-13-93 under the business name of GSI by (signature) Allison J. [unclear]					

INSTRUCTIONS. Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.