

1 LOCATION OF WATER WELL: County: Barton Fraction NW 1/4 NE 1/4 NE 1/4 Section Number 32 Township Number 19 Range Number 13 Distance and direction from nearest town or city street address of well if located within city? See below RW-2

2 WATER WELL OWNER: Express Lube RR#, St. Address, Box #: 2805 10th City, State, ZIP Code: Great Bend, KS 67530 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the NE section of the top-right 4-section block]

4 DEPTH OF COMPLETED WELL: 25 ft. ELEVATION: 1850 ft. WELL'S STATIC WATER LEVEL: 25 ft. below land surface measured on mo/day/yr Pump test data: Well water was 25 ft. after 25 hours pumping Est. Yield 25 gpm Well water was 25 ft. after 25 hours pumping Bore Hole Diameter 12 in. to 25 ft. and 25 in. to 25 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Recovery Well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded X Blank casing diameter 6 in. to 10 ft. Dia 3.68 in. to 25 ft. Dia 280 in. to 25 ft. Casing height above land surface 0 in. weight 3.68 lbs./ft. Wall thickness or gauge No. 280 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 10 ft. to 25 ft. From 8 ft. to 25 ft. GRAVEL PACK INTERVALS: From 8 ft. to 25 ft. From 8 ft. to 25 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 5 ft. From 5 ft. to 8 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage 25 oil bay Direction from well? NA How many feet? 25

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-22-93 and this record is true to the best of my knowledge and belief in Kansas Water Well Contractor's License No. 102 W This Water Well Record was completed on (mo/day/year) under the business name of Layne, Inc. by (signature) Steven R. Mitchell

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send two copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

1/2