


1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Barton		NE 1/4 NW 1/4 NE 1/4		33		T 19 S		R 13 E <u>(W)</u>	
Distance and direction from nearest town or city street address of well if located within city? 5212 Feet From North Line & 1242 Feet From West Line of Southeast Corner of Section 33 01928013 MW-3									
2 WATER WELL OWNER: Sanko Service RR#, St. Address, Box # : 1600 Tenth Street City, State, ZIP Code : Great Bend, KS 67530 Board of Agriculture, Division of Water Resources Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 16.0 ft. ELEVATION: Approximate Surface Elevation: 1846 ft. Depth(s) Groundwater Encountered 1. 11.0 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 10.54 ft. below land surface measured on mo/day/yr 04/30/92 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8.2 in. to 16.0 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>(10)</u> Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <u>X</u>							
									
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped <u>(2)</u> PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded <u>X</u> Blank casing diameter 2 in. to 16 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface -4 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40 TYPE OF SCREEN OR PERFORATION MATERIAL: <u>(7)</u> PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot <u>(3)</u> Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 6 ft. to 16 ft., From ft. to ft. From 4 ft. to 16 ft., From ft. to ft. GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft. From ft. to ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement <u>(2)</u> Cement grout <u>(3)</u> Bentonite 4 Other Grout Intervals: From 0 ft. to 2 ft., From 2 ft. to 4 ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy <u>(11)</u> Fuel storage 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below) Direction from well? South How many feet? Approximately 60 Feet									
LITHOLOGIC LOG					PLUGGING INTERVALS				
FROM	TO				FROM	TO			
0.0	0.5	Gravel							
0.5	3.5	Brown, Lean to Fat Clay, With Sand							
3.5	5.0	Brown, Fine to Medium Sand							
5.0	9.0	Tan-Brown, Fine Sand							
9.0	10.5	Tan-Brown, Fine to Coarse Sand							
10.5	11.0	Black-Gray-Green Silt							
11.0	16.0	Tan-Green, Fine to Medium Sand							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 04/30/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 04/30/92 under the business name of Terracon Consultants, Inc. by (signature) <i>Steve Fischer</i>									