

1 LOCATION OF WATER WELL:		Fraction		Form WWC-5		KSA 82a-1212	
County: Barton		NE 1/4 NW 1/4 NE 1/4		Section Number 33		Township Number T 1S S	
						Range Number R 13 EW	
Distance and direction from nearest town or city street address of well if located within city?							
5067 Feet From North Line & 1125 Feet From West Line of Southeast Corner of Section 33							01928013 MW-1
2 WATER WELL OWNER: Floyd Sanko							
RR#, St. Address, Box # : 1600 Tenth Street							Board of Agriculture, Division of Water Resources
City, State, ZIP Code : Great Bend, KS 67530							Application Number:
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 15.0 ft. ELEVATION: Approximate Surface Elevation: 1845.0					
		Depth(s) Groundwater Encountered 1. 10.0 ft. 2. ft. 3. ft.					
		WELL'S STATIC WATER LEVEL 9.35 ft. below land surface measured on mo/day/yr 04/29/92					
		Pump test data: Well water was ft. after hours pumping gpm					
		Est. Yield gpm: Well water was ft. after hours pumping gpm					
		Bore Hole Diameter 8.2 in. to 15.0 ft. and in. to ft.					
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well					
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted					
		Water Well Disinfected? Yes No X					
5 TYPE OF BLANK CASING USED:							
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped							
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded							
Blank casing diameter 2 in. to 15 ft. Dia in. to ft. Dia in. to ft.							
Casing height above land surface -3 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement							
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)							
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes							
SCREEN-PERFORATED INTERVALS: From 5 ft. to 15 ft. From ft. to ft.							
GRAVEL PACK INTERVALS: From 3 ft. to 15 ft. From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals: From 0 ft. to 1 ft. From 1 ft. to 3 ft. From ft. to ft.							
What is the nearest source of possible contamination:							
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well							
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well							
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)							
13 Insecticide storage							
Direction from well? Northwest How many feet? Approximately 280 Feet							
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS							
0.0 0.8 Concrete, Sand Base							
0.8 3.0 Brown, Lean to Fat Clay							
3.0 10.0 Green, Gray, Fine Sand							
10.0 11.0 Tan, Gray, White, Medium to Coarse Sand							
11.0 11.5 Tan, Gray, Fine Sand							
11.5 15.0 Fine to Medium Sand, Trace Coarse							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 04/29/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 04/29/92 under the business name of Terracon Consultants, Inc. by (signature) Steve Tucker							
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.							