

1 LOCATION OF WATER WELL: County: Barton		Fraction NE 1/4 NE 1/4 NW 1/4		Section Number 33		Township Number T 19 S		Range Number R 13 E (W)																															
Distance and direction from nearest town or city street address of well if located within city? Phillips 66 10th & Main Great Bend, KS.																																							
2 WATER WELL OWNER: Diane Bud RR#, St. Address, Box #: Bud 011 City, State, ZIP Code: 2001-10th Great Bend, KS. Board of Agriculture, Division of Water Resources Application Number:																																							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: 15'6" ft. ELEVATION:																																				
			Depth(s) Groundwater Encountered 1 9'6" ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 7.32 ft. below land surface measured on mo/day/yr 7-13-94 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8'6" in. to 15'6" ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only (10) Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes (No)																																				
			5 TYPE OF BLANK CASING USED:																																				
			1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded X Blank casing diameter 2.375 in. to 5' ft., Dia. in. to ft., Dia. in. SDR 13 ft. Casing height above land surface Flush Mount in., weight lbs./ft. Wall thickness or gauge No. SCH 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)																																				
			SCREEN-PERFORATED INTERVALS: From 15' ft. to 5' ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 15'6" ft. to 4' ft., From ft. to ft. From ft. to ft., From ft. to ft.																																				
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 4' ft. to 3' ft., From 3' ft. to 0' ft., From ft. to ft. What is the nearest source of possible contamination: (3) 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy (2) 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? East South East How many feet? 80'																																							
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>.75</td> <td>Concrete</td> <td></td> <td></td> <td></td> </tr> <tr> <td>.75</td> <td>6.25</td> <td>Dk greenish gray silty clay, moist, slight to mod. odor.</td> <td></td> <td></td> <td></td> </tr> <tr> <td>6.25</td> <td>11.25</td> <td>Fine-coarse grained green gray sand, mod odor, Wet at 9 1/2'</td> <td></td> <td></td> <td></td> </tr> <tr> <td>11.25</td> <td>15'6"</td> <td>Tan fine-coarse grained sand, wet, no odor.</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>										FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	.75	Concrete				.75	6.25	Dk greenish gray silty clay, moist, slight to mod. odor.				6.25	11.25	Fine-coarse grained green gray sand, mod odor, Wet at 9 1/2'				11.25	15'6"	Tan fine-coarse grained sand, wet, no odor.			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																		
0	.75	Concrete																																					
.75	6.25	Dk greenish gray silty clay, moist, slight to mod. odor.																																					
6.25	11.25	Fine-coarse grained green gray sand, mod odor, Wet at 9 1/2'																																					
11.25	15'6"	Tan fine-coarse grained sand, wet, no odor.																																					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-13-94 539 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. JB Environmental Drilling This Water Well Record was completed on (mo/day/yr) 7-21-94 under the business name of by (signature) James Becker																																							