

1 LOCATION OF WATER WELL: County: Barton		Fraction NW 1/4 SE 1/4 NW 1/4	Section Number 33	Township Number T 19 S	Range Number R 13 EW
Distance and direction from nearest town or city street address of well if located within city? 6th & Morton, Great Bend, Ks.					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code		City of Great Bend 1209 Williams Great Bend, K. 67530			
		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 15'6" ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1'9" ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 9'50" ft. below land surface measured on mo/day/yr 6-8-94 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8'6" in. to 15'6" ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only (10) Monitoring well 12 Other (Specify below)			
		Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel (2) PVC Blank casing diameter 2.375 in. to 5' ft. Dia in. to ft. Dia in. to SDR 13 Casing height above land surface Flush Mount in., weight lbs./ft. Wall thickness or gauge No. SCH 40		5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass Welded Threaded X			
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)		10 Other (specify)			
SCREEN OR PERFORATION OPENINGS ARE:		11 None (open hole)			
1 Continuous slot (3) Mill slot 2 Louvered shutter 4 Key punched		5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From 15' ft. to 5' ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 15'6" ft. to 4' ft., From ft. to ft. From ft. to ft., From ft. to ft.			
6 GROUT MATERIAL:		4 Other			
1 Neat cement (2) Cement grout (3) Bentonite Grout Intervals: From 4' ft. to 3' ft., From 3' ft. to 0' ft., From ft. to ft.		10 Livestock pens 14 Abandoned water well (11) Fuel storage Four 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage			
What is the nearest source of possible contamination:		How many feet? 0			
1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard					
Direction from well? In Old Tank Pit					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.75	Sand & Gravel Base			
.75	7.25	Fine-med dry sand, no odor, loose.			
7.25	9	Dk green-gray sandy silty clay, mottled, mod. diesel odor.			
9	15.50	Fine-coarse grained sand & gravel, wet, mod. to strong odor.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-6-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 6-9-94 under the business name of JB Environmental Drilling by (signature) James Becker					