

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Barton		NE ¼ NE ¼ NE ¼	33	T 19 S	R 13 EW
Distance and direction from nearest town or city street address of well if located within city?					
Taylor Food Mart 1615 10th St. Great Bend, Ks.					
2 WATER WELL OWNER: EZ Serve					
RR#, St. Address, Box #: P.O. Box 922021			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code: Houston, TX. 77292-2021			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 15'6" ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 8' ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 7.22 ft. below land surface measured on mo/day/yr 5-9-94			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
Bore Hole Diameter 8 1/2" in. to 15'6" ft. and in. to ft.		WELL WATER TO BE USED AS:			
1 Domestic		3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation		4 Industrial	7 Lawn and garden only	10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☒ If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes ☒ No ☒					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	CASING JOINTS: Glued Clamped
2 PVC		4 ABS	7 Fiberglass		Welded
Blank casing diameter 2.375 in. to 5'		ft. Dia in. to ft. Dia in. to ft.			
Casing height above land surface 2 1/2 ft. weight lbs./ft. Wall thickness or gauge No. SDR 13					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
3 Mill slot			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS:					
From 15' ft. to 5' ft.		ft. From ft. to ft.			
GRAVEL PACK INTERVALS:					
From 15'6" ft. to 4' ft.		ft. From ft. to ft.			
From ft. to ft.		ft. From ft. to ft.			
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout	3 Bentonite	4 Other	
Grout Intervals: From 4' ft. to 3' ft.		ft. From ft. to ft.			
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	11 Fuel storage Father	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	13 Insecticide storage	16 Other (specify below)
Direction from well? In old Tank pit		How many feet? 0			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Ls.Rx. Gravel			
1	9	Fine-coarse Grained fill sand, wet at 8'. Strong odor.			
9	15.25	Dk gray sand & gravel, wet, strong odor, subrounded to poorly sorted grains. Wet at 8'.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) ☒ constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-9-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 5-14-94 under the business name of JB Environmental Drilling by (signature) James Broken					