

1 LOCATION OF WATER WELL: County: Barton	Fraction NW $\frac{1}{4}$ NW $\frac{1}{4}$ NW	Section Number 34	Township Number T 19 S	Range Number R 13 EW
--	---	-----------------------------	----------------------------------	--------------------------------

Distance and direction from nearest town or city street address of well if located within city?

SE corner of 10th Street and Walnut Street

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code	Shirley Luther RR 4, Box 14 Great Bend, Ks. 67530	Board of Agriculture, Division of Water Resources Application Number:
---	--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 27 ft. ELEVATION: NA
--	---

Depth(s) Groundwater Encountered 1. **10** ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter: **10** in. to **38** ft., and in. to ft.

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Monitoring well	air sparging

Was a chemical/bacteriological sample submitted to Department? Yes No **X**; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No **X**

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
------------------------------	----------------	-----------------	------------------------------

1 Steel

2 PVC

Blank casing diameter **8** in. to **7** ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface **18** in., weight lbs./ft. Wall thickness or gauge No. **sch. 40**

3 RMP (SR)

4 ABS

6 Asbestos-Cement

7 Fiberglass

9 Other (specify below)

Welded

Threaded **X**

TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement
---	--------------	--------------------

1 Steel

2 Brass

3 Stainless steel

4 Galvanized steel

5 Fiberglass

6 Concrete tile

8 RMP (SR)

9 ABS

11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

2 Louvered shutter

3 Mill slot

4 Key punched

5 Gauzed wrapped

6 Wire wrapped

7 Torch cut

8 Saw cut

9 Drilled holes

10 Other (specify)

11 None (open hole)

SCREEN-PERFORATED INTERVALS:	From 7 ft. to 27 ft., From ft. to ft., From ft. to ft., From ft. to ft.
GRAVEL PACK INTERVALS:	From 5 ft. to 38 ft., From ft. to ft., From ft. to ft., From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
-------------------	---------------	-----------------------	--------------------	---------

Grout Intervals: From **0** ft. to **4** ft., From **4** ft. to **5** ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	16 Other (specify below)

Direction from well? **southwest**

How many feet? **115**

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1'	cl, v dk brn, org rich v slty, tr v f snd			
1'	4.5	cl, v dk brn, non-org, v slty, tr v f snd			
4.5	7	cl, lt brn, v slty, tr f-c snd, semiplst			
7	8	cl, lt brn, med-v sndy, v f-med grnd, v slty			
8	12	snd, v f-med grnd, tr of c grns, lt gry			
12	27	snd, f-c grnd, sl grvl, prly srtd, yell-brn clrd			
27	38	cl, yell-orang brn, v slty, v tight			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 01-05-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 02-11-94 under the business name of GeoCore Services, Inc. by (signature) <i>Dale Roll</i>
--