

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Barton	NW 1/4 NW 1/4 NW 1/4	34	T 19 S	R 13 EW

Distance and direction from nearest town or city street address of well if located within city?

SE corner of 10th Street and Walnut Street

2 WATER WELL OWNER:	Shirley Luther RR 4, Box 14 Great Bend, Ks. 67530	Board of Agriculture, Division of Water Resources Application Number:
---------------------	---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 27 ft. ELEVATION: NA
	Depth(s) Groundwater Encountered 1. 10 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter: 7 5/8 in. to 48 ft. and in. to ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well air sparging	
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes No X	

5 TYPE OF BLANK CASING USED:	5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
1 Steel 3 RMP (SR)	6 Asbestos-Cement 9 Other (specify below) Welded
2 PVC 4 ABS	7 Fiberglass Threaded X
Blank casing diameter 1 1/4 in. to 25 ft. Dia in. to ft. Dia in. to ft.	
Casing height above land surface 0 in. weight lbs./ft. Wall thickness or gauge No. sch. 40	
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 25 ft. to 27 ft. From ft. to ft.	
GRAVEL PACK INTERVALS: From 23 ft. to 28 ft. From ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 3 ft. From 3 ft. to 23 ft. From ft. to ft.	
What is the nearest source of possible contamination:	10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage	
Direction from well? north How many feet? 15	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6"	concrete			
6"	2'	snd, v f-med grnd, frly well srted, v slty, sl clayey, lt brn (fill)			
2	8'	clay, med brn-gry, sl-mod slty, tr v f snd			
8	9	snd, v f-med grnd, sl clayey, v slty, med gry			
9	20	snd, f-c grnd, frly well srted, sl clayey, v slty gry			
20	27	snd, f-c grnd, frly well srted, sl clayey, v slty gry, sl grv			
27	28	clay, lt brn, mod-v slty, semiplstc			

AS6-flush mount cover

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-30-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 02-11-94 under the business name of GeoCore Services, Inc. by (signature) <i>Dale Rolf</i>
--