

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Barton	NW $\frac{1}{4}$ NW $\frac{1}{4}$ NW $\frac{1}{4}$	34	T 19 S	R 13 EW

Distance and direction from nearest town or city street address of well if located within city?

10th Street and Walnut Street

2 WATER WELL OWNER:	Shirley Luther	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	RR 4, Box 14	Application Number:
City, State, ZIP Code :	Great Bend, Ks. 67530	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 27 ft. ELEVATION: NA
	Depth(s) Groundwater Encountered 1. 10 ft. 2. . ft. 3. . ft. WELL'S STATIC WATER LEVEL . ft. below land surface measured on mo/day/yr Pump test data: Well water was . ft. after . hours pumping . gpm Est. Yield . gpm: Well water was . ft. after . hours pumping . gpm Bore Hole Diameter: 7 5/8 in. to 48 ft., and . in. to . ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only (10) Monitoring well air sparging Was a chemical/bacteriological sample submitted to Department? Yes. . No. X .; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes . No X .

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued . . . Clamped . . .
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
(2) PVC	4 ABS	7 Fiberglass	Welded . . .
Blank casing diameter . 1 1/4 in. to 25 ft. Dia . in. to . ft. Dia . in. to . ft.			Threaded. X .
Casing height above land surface . 0 in. weight . lbs./ft. Wall thickness or gauge No. sch. 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	(3) Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	(3) Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From . 25 ft. to . 27 ft. From . ft. to . ft.			
GRAVEL PACK INTERVALS: From . 22 ft. to . 28 ft. From . ft. to . ft.			

6 GROUT MATERIAL:	1 Neat cement	(2) Cement grout	(3) Bentonite	4 Other
Grout Intervals: From . 0 ft. to . 5 ft. From . 5 ft. to . 22 ft. From 28 ft. to 48 ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	(11) Fuel storage
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	14 Abandoned water well
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	15 Oil well/Gas well
Direction from well?	excavation			16 Other (specify below)
				13 Insecticide storage
				How many feet? 0

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6"	concrete			
6"	5'	fill snd, f-c grnd, frly well srted, sloder			
5	8'	cly, v dk brn, tr f-c snd, sl-mod slty			
8	18	snd, f-med grnd, v dk gry, rnd-subang, v slty, tr grvl & c snd			
18	27	snd, f-c grnd, sl-mod grvl, prly srted, v slty, rnd-subang, med gry			
27	48	cly, mod-v slty, lt-med brn			

AS5-flush mount cover

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-29-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 02-11-94 under the business name of GebCore Services, Inc. by (signature) <i>Dale Roh</i>
