

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Barton	NW 1/4 NW 1/4 NW 1/4	34	T 19 S	R 13 EW

Distance and direction from nearest town or city street address of well if located within city?

10th Street and Walnut Street

2 WATER WELL OWNER:	Shirley Luther	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	RR 4, Box 14	Application Number:
City, State, ZIP Code :	Great Bend, Ks. 67530	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 26 ft. ELEVATION: NA
	Depth(s) Groundwater Encountered 1. 10 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter: 7 5/8 in. to 28 ft., and in. to ft.
WELL WATER TO BE USED AS:	
5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well air sparging	
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes No X	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded Threaded X
Blank casing diameter 1 1/4 in. to 24 ft., Dia in. to ft., Dia in. to ft.			
Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No. sch. 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	7 PVC
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)
			10 Asbestos-cement
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
		7 Torch cut	11 None (open hole)
SCREEN-PERFORATED INTERVALS: From 24 ft. to 26 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 22 ft. to 28 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 3 ft., From 3 ft. to 22 ft., From ft. to ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? north				
How many feet? 80				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	silt, yell-oran, sl-mod cly, mod-v			
		sndy, f-v f grnd, sl grvl			
1	5	cly, v drk brn, v slty, semiplastic			
5	7	cly, v slty, lt-med gry, mod-v			
		sndy, v f-f grnd			
7	13	snd, v f-med grnd, tr c grns, v			
		slty, sl clyey			
13	26	snd, f-c grnd, sl-mod grvl, prly strd,			
		lt gry-brn			
26	28	cly, yell-orang brn, v slty, v tight			
AS1-flush mount cover					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 01-04-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 02-11-94 under the business name of GeoCore Services, Inc. by (signature) <i>Dale Koll</i>	
---	--