

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: BARTON	NE 1/4 NE 1/4 NW 1/4	34	T 19 S	R 13 EW

Distance and direction from nearest town or city street address of well if located within city?

1331 10TH STREET, GREAT BEND, KS**MW-1**

2 WATER WELL OWNER:	RR#, St. Address, Box #	City, State, ZIP Code	Board of Agriculture, Division of Water Resources
MUSKET	10601 N. PENNSYLVANIA	OKLAHOMA CITY, OK 73126	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	ELEVATION:
	17 ft.	
	Depth(s) Groundwater Encountered	1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL	8.7 ft. below land surface measured on mo/day/yr 6-28-90
	Pump test data: Well water was	ft. after hours pumping gpm
	Est. Yield gpm: Well water was	ft. after hours pumping gpm
	Bore Hole Diameter	in. to ft., and in. to ft.
	WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
	2 Irrigation 4 Industrial 7 Lawn and garden only	0 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes No X	If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes No X	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded Threaded X
Blank casing diameter	in. to ft., Dia	in. to ft., Dia	in. to ft., Dia
Casing height above land surface	2.2 (FLUSH) in., weight	lbs./ft. Wall thickness or gauge No. 40	
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 17 ft. to 7 ft.	From ft. to ft.	
	From ft. to ft.	From ft. to ft.	
GRAVEL PACK INTERVALS:	From 17 ft. to 5 ft.	From ft. to ft.	
	From ft. to ft.	From ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:	3 From 5 ft. to 3 ft.	2 From 3 ft. to 0 ft.	From ft. to ft.	
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well?	S			How many feet? 80

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	CLAY			
5	10	SILTY SAND			
10	17	SAND			
GROUT & CASING VARIANCE GRANTED					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:	This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/15/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 517 This Water Well Record was completed on (mo/day/yr) 1-10-91 under the business name of GROWING WATER TECHNOLOGY INC by (signature) Albert Stout
--	---

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4