

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Barton		1/4 1/4 NW 1/4		34		T 19 S		R 13 EW	
Distance and direction from nearest town or city street address of well if located within city?									
700 Fry St. in City of Great Bend, Ks/									
2 WATER WELL OWNER:									
RR#, St. Address, Box #: Acme Pipe and Steel Co. Board of Agriculture, Division of Water Resources									
City, State, ZIP Code: 700 Fry St. Great Bend, Ks. 67530 Application Number: 669									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: 75 ft. ELEVATION:						
			Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.						
			WELL'S STATIC WATER LEVEL 12 ft. below land surface measured on mo/day/yr 5-13-92						
			Pump test data: Well water was ft. after hours pumping gpm						
			Est. Yield na gpm Well water was ft. after hours pumping gpm						
			Bore Hole Diameter 10 in. to 75 ft. and in. to ft.						
WELL WATER TO BE USED AS:									
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)									
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well									
Was a chemical/bacteriological sample submitted to Department? Yes No. X; If yes, mo/day/yr sample was submitted									
Water Well Disinfected? Yes hth No									
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped									
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded									
Blank casing diameter 5 in. to 60 ft. Dia in. to ft. Dia in. to ft.									
Casing height above land surface 2' in. weight 258 lbs./ft. Wall thickness or gauge No.									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 60 ft. to 75 ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 12 ft. to 75 ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hole plug									
Grout Intervals: From 0 ft. to 12 ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
13 Insecticide storage Cement slab w/batteries 80' stacked on it.									
Direction from well? south west How many feet?									
FROM TO		LITHOLOGIC LOG		FROM TO		PLUGGING INTERVALS			
0	5	Top soil							
5	10	Tan clay							
10	26	Sand and gravel							
26	35	Sand and gravel with thin clay streak							
35	55	Sand and gravel small to medium							
55	75	Sand and gravel coarse							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-14-92 and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 6-3-92									
under the business name of Rosencrantz-Bemis by (signature) Freda Haden									