

MW-3 2011043		WATER WELL RECORD Form WWC-5 KSA 82a-1212	
1 LOCATION OF WATER WELL:		Fraction	Section Number
County: Barton		NW 1/4 NW 1/4 NW 1/4	34
Distance and direction from nearest town or city street address of well if located within city?		Township Number	Range Number
1221 10th Street, Great Bend		T 19 S	R 13 EW
2 WATER WELL OWNER:			
RR#, St. Address, Box #		Board of Agriculture, Division of Water Resources	
City, State, ZIP Code		Application Number:	
OKlahoma City, OK 73126			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL	
		15 ft. ELEVATION:	
		Depth(s) Groundwater Encountered 1 8.5 ft. 2 ft. 3 ft.	
		WELL'S STATIC WATER LEVEL 9.12 ft. below land surface measured on mo/day/yr 2-25-93	
		Pump test data: Well water was ft. after hours pumping gpm	
		Est. Yield gpm Well water was ft. after hours pumping gpm	
		Bore Hole Diameter 8 in. to ft. and in. to ft.	
		WELL WATER TO BE USED AS:	
		5 Public water supply 8 Air conditioning 11 Injection well	
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted	
		Water Well Disinfected? Yes No X	
5 TYPE OF BLANK CASING USED:			
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped			
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded			
7 Fiberglass Threaded Flush			
Blank casing diameter 2 in. to ft. Dia 7 PVC 10 Asbestos-cement			
Casing height above land surface Flush in. weight 703 lbs./ft. Wall thickness or gauge No. 154			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes			
7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 5.0 ft. to 15.0 ft. From ft. to ft.			
GRAVEL PACK INTERVALS: From 4.0 ft. to 15.0 ft. From ft. to ft.			
6 GROUT MATERIAL:			
1 Neat cement 2 Cement grout 3 Bentonite 4 Other			
Grout Intervals: From 4.0 ft. to 1.0 ft. From ft. to ft.			
What is the nearest source of possible contamination:			
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)			
13 Insecticide storage			
Direction from well? NE How many feet? 350			
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS	
0.0 4.5 Silt, clayey			
4.5 13.5 Sand, medium grain, well sorted			
13.5 15.0 Sand & gravel, coarse			
Flush mount waiver granted 12-17-92 for Love's Country Store #11; KDHE 06005391 by Don Taylor			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-25-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No 531 This Water Well Record was completed on (mo/day/yr) 3-9-93 under the business name of GSI by (signature) Allison Irwin			