

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Barton	NE 1/4 SE 1/4 SW 1/4	35	T 19 S	R 13 EW

Distance and direction from nearest town or city street address of well if located within city?

Approximately 1/2 mile south and 2 miles east of Great Bend

2 WATER WELL OWNER:	Dale Weller	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	Route 2 - Box 10A	Application Number: N/A
City, State, ZIP Code :	Great Bend, KS 67530	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 67 ft. ELEVATION: unknown
	Depth(s) Groundwater Encountered 1. 20 ft. 2. 57 ft. 3. ft. WELL'S STATIC WATER LEVEL 10 ft. below land surface measured on mo/day/yr Pump test data: Well water was not ch'd ft. after hours pumping gpm Est. Yield unknown gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 in. to 67 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to 57 ft., Dia			Threaded
Casing height above land surface 24 in., weight 2.36 lbs./ft.			Wall thickness or gauge No. 214
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 57 ft. to 67 ft.	From ft. to ft.	
GRAVEL PACK INTERVALS:	From 20 ft. to 33 ft.	From ft. to ft.	
	From 40 ft. to 67 ft.	From ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other Bentonite Hole Plug
Grout Intervals:	From 3 ft. to 20 ft.	From ft. to ft.	From 33 ft. to 40 ft.	
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well? W				How many feet? 50

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	8	Topsoil and clay, brown			
8	24	Sand and Gravel, medium to fine to coarse			
24	48	Clay, greenish-gray			
48	50	Clay, tan, soft			
50	54	Sand and Gravel, medium to fine			
54	55	Clay, yellow			
55	67	Sand and Gravel, medium to fine			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:	This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-20-90 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 185	This Water Well Record was completed on (mo/day/yr) 2-21-90
under the business name of Clarke Well & Equipment, Inc.	by (signature) <i>Clarke Well & Equipment, Inc.</i>

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.