

1) LOCATION OF WATER WELL: County: <u>Barton</u>		Fraction <u>SW 1/4 NE 1/4 SW 1/4</u>	Section Number <u>29</u>	Township Number <u>T 19 S</u>	Range Number <u>R 13W E/W</u>
Distance and direction from nearest town or city street address of well if located within city? <u>downtown Great Bend, Ks.</u>					
2) WATER WELL OWNER: <u>Dominican Sisters</u> RR#, St. Address, Box # : <u>3600 Broadway</u> City, State, ZIP Code : <u>Great Bend, Ks. 67530</u>					
Board of Agriculture, Division of Water Resources Application Number:					
3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4) DEPTH OF COMPLETED WELL: <u>69</u> ft. ELEVATION: <u>unknown</u>			
1 Mile		Depth(s) Groundwater Encountered 1. <u>13</u> ft. 2. <u>13</u> ft. 3. <u>13</u> ft. WELL'S STATIC WATER LEVEL <u>13</u> ft. below land surface measured on mo/day/yr <u>04/25/01</u> Pump test data: Well water was <u>350</u> gpm: Well water was <u>24</u> in. to <u>69</u> ft. and <u>69</u> ft. after <u>04/25/01</u> hours pumping <u>350</u> gpm Bore Hole Diameter <u>24</u> in. to <u>69</u> ft. and <u>69</u> ft. to <u>69</u> ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes <u>No</u> ; If yes, mo/day/yr sample was submitted <u>mitted</u> Water Well Disinfected? Yes <u>No</u>			
5) TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: <u>Glued</u> <u>Clamped</u> 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) <u>Welded</u> Blank casing diameter <u>12</u> in. to <u>48</u> ft. Dia <u>12</u> in. to <u>48</u> ft. Dia <u>12</u> in. to <u>48</u> ft. Dia <u>12</u> in. to <u>48</u> ft. Dia Casing height above land surface <u>12</u> in., weight <u>2.8</u> lbs./ft. Wall thickness or gauge No. <u>Sch. 40</u> TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From <u>48</u> ft. to <u>68</u> ft. From <u>48</u> ft. to <u>68</u> ft. From <u>48</u> ft. to <u>68</u> ft. From <u>48</u> ft. to <u>68</u> ft. GRAVEL PACK INTERVALS: From <u>22</u> ft. to <u>36</u> ft. From <u>40</u> ft. to <u>69</u> ft. From <u>40</u> ft. to <u>69</u> ft. From <u>40</u> ft. to <u>69</u> ft.					
6) GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From <u>0</u> ft. to <u>5</u> (2) ft. From <u>5</u> ft. to <u>22</u> (3) ft. From <u>36</u> ft. to <u>40</u> (3) ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) <u>none - in yard</u> Direction from well? How many feet? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 1 top soil 1 5 clay 5 19 1/2 sand and gravel 19 1/2 22 clay 22 36 sand and gravel 36 47 clay 47 65 sand and gravel					
7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>04/25/01</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>186</u> This Water Well Record was completed on (mo/day/yr) <u>05/14/01</u> under the business name of <u>Kelly's Water Well Service, Inc.</u> by (signature) <u>Kathryn R. Wood</u>					