

1 LOCATION OF WATER WELL: Fraction		Section Number		Township Number		Range Number	
County: Barton SW ¼ NW ¼ SE ¼		6		T 19 S		R 13 ☒ W	
Distance and direction from nearest town or city street address of well if located within city? 3 1/4 North of Great Bend							
2 WATER WELL OWNER: Shannon D. Donovan				# BT10, # 9036			
RR#, St. Address, Box #: P.O. Box 894				Board of Agriculture, Division of Water Resources			
City, State, ZIP Code: Great Bend, KS 67530				Application Number: 20,683			
3 LOCATE WELL'S LOCATION WITH		4 DEPTH OF COMPLETED WELL: 136 ft. ELEVATION:					
AN "X" IN SECTION BOX:		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.					
		WELL'S STATIC WATER LEVEL: 40 ft. below land surface measured on mo/day/yr 7-30-01					
		Pump test data: Well water was 72 ft. after 5 hours pumping 1250 gpm					
		Est. Yield 1500 gpm: Well water was 66 ft. after 3 hours pumping 860 gpm					
		Bore Hole Diameter: 28 in. to 135 ft., and in. to ft.					
		WELL WATER TO BE USED AS:					
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
		2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well					
		Was a chemical/bacteriological sample submitted to Department? Yes. No. ☒ ; If yes, mo/day/yr sample was submitted					
		Water Well Disinfected? Yes No ☒					
5 TYPE OF BLANK CASING USED:							
1 Steel		3 RMP (SR)		5 Wrought iron		8 Concrete tile	
2 PVC		4 ABS		6 Asbestos-Cement		9 Other (specify below)	
Blank casing diameter 16 in. to 88 ft., Dia						CASING JOINTS: Glued. ☒ Clamped.	
Casing height above land surface 12 in., weight sch 40						Welded.	
TYPE OF SCREEN OR PERFORATION MATERIAL:						Threaded.	
1 Steel		3 Stainless steel		5 Fiberglass		7 PVC	
2 Brass		4 Galvanized steel		6 Concrete tile		8 RMP (SR)	
						10 Asbestos-cement	
						11 Other (specify)	
						12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot		3 Mill slot		5 Gauzed wrapped		8 Saw cut	
2 Louvered shutter		4 Key punched		6 Wire wrapped		9 Drilled holes	
				7 Torch cut		10 Other (specify)	
						11 None (open hole)	
SCREEN-PERFORATED INTERVALS: From 88 ft. to 135 ft., From ft. to ft.							
GRAVEL PACK INTERVALS: From 135 ft. to 20 ft., From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hole plug							
Grout intervals: From 20 ft. to 0 ft., From ft. to ft., From ft. to ft.							
What is the nearest source of possible contamination:							
1 Septic tank		4 Lateral lines		7 Pit privy		10 Livestock pens	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		11 Fuel storage	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		12 Fertilizer storage	
						13 Insecticide storage	
						14 Abandoned water well	
						15 Oil well/Gas well	
						16 Other (specify below)	
						None	
Direction from well?						How many feet?	
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS	
0	2	top soil soil					
2	8	brown clay					
8	17	brown and tan clay					
17	37	tan clay					
37	51	tan and gray clay					
51	57	fine sand					
57	69	sand and gravel small, clean, loose					
69	78	gray clay					
78	86	sand and gravel, clay mixed					
86	122	sand and gravel small, clean, loose					
122	123	brown clay					
123	132	sand and gravel, small, clean, loose					
132	135	sand and gravel, clay mixed					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-28-01 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 134 This Water Well Record was completed on (mo/day/yr) 9-5-01 under the business name of Rosencrantz-Bemis by (signature) Fredis Dodson							