

1 LOCATION OF WATER WELL: County: Barton		Fraction SE 1/4 SW 1/4 SE 1/4	Section Number 20	Township Number T 19 S	Range Number R 13w E/W
Distance and direction from nearest town or city street address of well if located within city? downtown Great Bend, KS					
2 WATER WELL OWNER: Jim Mayberry RR#, St. Address, Box # : 5906 16th St. Terr. City, State, ZIP Code : Great Bend, KS 67530 Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 47 ft. ELEVATION: unknown			
		Depth(s) Groundwater Encountered 1 15 ft. 2 15 ft. 3 15 ft. WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr 09/30/05 Pump test data: Well water was 40 gpm. Well water was 40 gpm. Est. Yield 40 gpm. Well water was 40 gpm. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes Yes No			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded Blank casing diameter 5 in. to 37 ft., Dia 37 in. to 40 ft., Dia 40 in. to 40 ft. Casing height above land surface 12 in., weight 2.3 lbs./ft. Wall thickness or guage No. Sch. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 37 ft. to 47 ft., From 37 ft. to 47 ft., From 37 ft. to 47 ft.					
GRAVEL PACK INTERVALS: From 23 ft. to 30 ft., From 34 ft. to 47 ft., From 34 ft. to 47 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 23 ft., From 34 ft. to 47 ft., From 34 ft. to 47 ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? South 13 Insecticide storage house How many feet? 10					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	top soil			
3	8	clay			
8	22	sand and gravel			Location OK'd by Barton Co. Environmental
22	23	clay			
23	30	sand and gravel			
30	35	clay			
35	47	sand and gravel			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 09/30/05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 186 . This Water Well Record was completed on (mo/day/yr) 10/03/05 under the business name of Kelly's Water Well Service, Inc. by (signature) <i>Kathryn L Good</i>					