

1 LOCATION OF WATER WELL:		Fraction	WATER WELL RECORD FORM WWC-3		Section Number	Township Number	Range Number
County: Barton		<u>SE</u> $\frac{1}{4}$ SW $\frac{1}{4}$ SW $\frac{1}{4}$			27	T 19 S	R 13 E
Distance and direction from nearest town or city street address of well if located within city? <u>35'S, 24'E of SW corner of truck repair bldg; 624 E. 10th St</u>							
2 WATER WELL OWNER: Dorothy Morrison c/o Glenopie Conner & Opie RR#, St. Address, Box # P.O. Drawer E City, State, ZIP Code Great Bend, KS 67530							
Board of Agriculture, Division of Water Resources Application Number:							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 13.5 ft. ELEVATION: 1840.16 TOC					
A 2x2 grid representing a section box. The quadrants are labeled NW, NE, SW, SE. An 'X' is marked in the SW quadrant.		Depth(s) Groundwater Encountered 1. 8 ft. 2. ft. 3. ft.					
		WELL'S STATIC WATER LEVEL 7.14 ft. below land surface measured on mo/day/yr 2-12-98					
		Pump test data: Well water was ft. after hours pumping gpm					
		Est. Yield gpm: Well water was ft. after hours pumping gpm					
		Bore Hole Diameter 8 in. to 13.5 ft. and in. to ft.					
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>10 Monitoring well</u>					
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted					
		Water Well Disinfected? Yes No X					
5 TYPE OF BLANK CASING USED:							
1 Steel		3 RMP (SR)		5 Wrought iron		8 Concrete tile	
<u>2 PVC</u>		4 ABS		6 Asbestos-Cement		9 Other (specify below)	
				7 Fiberglass		CASING JOINTS: Glued Clamped Welded Threaded flush	
Blank casing diameter 2 in. to 3.5 ft. Dia in. to ft. Dia in. to ft.							
Casing height above land surface flush in. weight 0.703 lbs./ft. Wall thickness or gauge No. Sch 40							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel		3 Stainless steel		5 Fiberglass		8 RMP (SR)	
2 Brass		4 Galvanized steel		6 Concrete tile		9 ABS	
						10 Asbestos-cement	
						11 Other (specify)	
						12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot		<u>3 Mill slot</u>		5 Gauzed wrapped		8 Saw cut	
2 Louvered shutter		4 Key punched		6 Wire wrapped		9 Drilled holes	
				7 Torch cut		10 Other (specify)	
						11 None (open hole)	
SCREEN-PERFORATED INTERVALS:							
From 3.5 ft. to 13.5 ft.		From 3.5 ft. to 13.5 ft.		From 3.5 ft. to 13.5 ft.		From 3.5 ft. to 13.5 ft.	
GRAVEL PACK INTERVALS:							
From 2.5 ft. to 13.5 ft.		From 2.5 ft. to 13.5 ft.		From 2.5 ft. to 13.5 ft.		From 2.5 ft. to 13.5 ft.	
6 GROUT MATERIAL:							
1 Neat cement		2 Cement grout		<u>3 Bentonite</u>		4 Other	
Grout Intervals: From 0.5 ft. to 2.5 ft. From 0.5 ft. to 2.5 ft. From 0.5 ft. to 2.5 ft. From 0.5 ft. to 2.5 ft.							
What is the nearest source of possible contamination:							
1 Septic tank		4 Lateral lines		7 Pit privy		10 Livestock pens	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		11 Fuel storage	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		12 Fertilizer storage	
						13 Insecticide storage	
						14 Abandoned water well	
						15 Oil well/Gas well	
						16 Other (specify below)	
Direction from well? How many feet?							
LITHOLOGIC LOG				PLUGGING INTERVALS			
FROM	TO			FROM	TO		
0	2.5	Clay, m-h plasticity					
2.5	8	Clay, l-m plasticity					
8	13.5	Sand, vf-f grained					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/19/98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 3/20/98 under the business name of GSI by (signature) Candace Watson							