


1 LOCATION OF WATER WELL: County: Barton	Fraction SE 1/4 SE 1/4 NW 1/4	Section Number 28	Township Number T 19 S	Range Number R 13 EW
--	---	-----------------------------	----------------------------------	--------------------------------

Distance and direction from nearest town or city street address of well if located within city?

In town

2 WATER WELL OWNER: Kansas Oil RR#, St. Address, Box #: 17th + Washington City, State, ZIP Code: Great Bend, Ks.	Board of Agriculture, Division of Water Resources Application Number:
---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 17' ft. ELEVATION: Depth(s) Groundwater Encountered 1. 8 1/2' ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: 8.60 ft. below land surface measured on mo/day/yr 3-23-98 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: 8 1/2" in. to 17' ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No
---	--

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC Blank casing diameter 2.375 in. to 4' ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface Flush Mt. in., weight lbs./ft. Wall thickness or gauge No. SDR-13 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 14' ft. to 4' ft., From ft. to ft. GRAVEL PACK INTERVALS: From 17' ft. to 3' ft., From ft. to ft.	CASING JOINTS: Glued Clamped Welded Threaded X
--	---

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 3' ft. to 1' ft., From 1' ft. to 0' ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 1 Fuel storage FOUER 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? South How many feet? 80'
--

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2.0	Dark brown clay, sandy silt, moist			
2.0	6.5	Dark brown silt, trace caliche, soft			
6.5	8.5	Dark brown to black silt, moist			
8.5	14.0	Dark silt w/ fine sand, wet soft			
14.0	17.0	Fire-crushed sand & gravel, black sub angular, well graded			

F.M. OK'd by Don Taylor

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-24-98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 4-8-98 under the business name of SB Environmental Drilling by (signature) James Baker
