

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Barton	NW 1/4 NW 1/4 NW	34	T 19 S	R 13 E

Distance and direction from nearest town or city street address of well if located within city?

SW corner of Walnut and 10 Streets

2 WATER WELL OWNER:	Shirley Luther	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	RR 4, Box 14	Application Number:
City, State, ZIP Code :	Great Bend, Ks. 67530	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 27 ft. ELEVATION: NA
	Depth(s) Groundwater Encountered 1. 10 ft. 2. . ft. 3. . ft.
	WELL'S STATIC WATER LEVEL . ft. below land surface measured on mo/day/yr
	Pump test data: Well water was . ft. after . hours pumping . gpm
	Est. Yield . gpm Well water was . ft. after . hours pumping . gpm
	Bore Hole Diameter: 10 in. to 27 ft., and . in. to . ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well air sparging	
Was a chemical/bacteriological sample submitted to Department? Yes. . No. x . If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes . No x	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued . . . Clamped . . .
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded . . .
Blank casing diameter . 8 in. to 7 ft., Dia . in. to . ft., Dia . in. to . ft.			Threaded. x
Casing height above land surface . 18 in., weight . lbs./ft. Wall thickness or gauge No. sch. 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	2 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS: From . 7 ft. to 27 ft., From . ft. to . ft.			
GRAVEL PACK INTERVALS: From . 6 ft. to 37 ft., From . ft. to . ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other . . .
Grout Intervals: From . 0 ft. to 4 ft., From . 4 ft. to 6 ft., From . ft. to . ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	16 Other (specify below)
Direction from well? northwest				
How many feet? 60				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1'	cly, v dk brn, v slty, org rich, tr f-c snd			
1	4'	cly, v dk brn, v slty, non-org, tr f-c snd			
4	7	cly, lt brn, v slty, tr v f-c snd			
7	15	snd, v f-med grnd w/tr-sl c grns, rnd-subang, gry in clr			
15	27	snd, f-c grnd, sl-mod grvl, rnd-subang, gry			
27	37	cly, lt yell-orang brn, v slty, tight			
RW1-above ground cover					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) . 01-05-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. . 527 This Water Well Record was completed on (mo/day/yr) 02-11-94 under the business name of GeoCore Services, Inc. by (signature) <i>Don Roll</i>
