			WWC-5		ision of Water	ļ			
			ge in Well Use		urces App. No		Well ID		
1 LOCATION OF WATER WELL: Fraction					tion Number 27	A			
County.						T 19 S	R 13 □E ■ W		
			First:		Street or Rural Address where well is located (if unknown, distance and				
Address:					irection from nearest town or intersection): If at owner's address, check here:				
Address:	Address: 1/6 NE					NE 10 Avenue, Great Bend			
City:	Great Be	nd State: KS	ZIP: 67530						
3 LOCATE WELL 4 DEPTH OF COMPLETED WELL:60.					5 Lotitue	38.37233	38 (411-4)		
	WIII A III Donth(s) Groundwater Encountered: 1)					5 Latitude: 38.372338 (decimal degrees) Longitude: 98.754920 (decimal degrees)			
	SECTION BOX:					Horizontal Datum: □ WGS 84 ■ NAD 83 □ NAD 27			
	WELL'S STATIC WATER LEVEL:6.1/2 f					Source for Latitude/Longitude:			
	■ below land surface, measured on (mo-day-yr)						·		
NW	above land surface, measured on (mo-day-yr)					(WAAS enabled? □			
7	Pump test data: Well water was					nd Survey Topogra			
W	E		s pumping		☐ On	line Mapper:			
SW	SE		s pumping						
		Estimated Yield:	stimated Yield:gpm			on:ft.	☐ Ground Level ☐ TOC		
S Bore Hole Diameter			10 in. to60	ft. and		Source: Land Survey GPS Topographic Map			
1 1	1 mile in. to ft.								
7 WELL WATER TO BE USED AS:									
 Domestic 									
☐ House		6. Dewatering: how many wells?				11. Test Hole: well ID			
	n & Garden 7. Aquifer Recharge: well ID					☐ Cased ☐ Uncased ☐ Geotechnical			
Livesto						12. Geothermal: how many bores?			
2. ☐ Irrigati 3. ☐ Feedlo		9. Environmental Remediation: well ID				a) Closed Loop ☐ Horizontal ☐ Vertical b) Open Loop ☐ Surface Discharge ☐ Inj. of Water			
Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ■ No If yes, date sample was submitted:									
8 TYPE OF CASING USED: ☐ Steel ■ PVC ☐ Other									
Casing diameter 5 in. to 60 ft., Diameter in. to ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 18 in. Weight SDR-26 lbs/ft. Wall thickness or gauge No.									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
☐ Steel ☐ Stainless Steel ☐ Fiberglass ■ PVC ☐ Other (Specify)									
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
☐ Continuous Slot ☐ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)									
□ Louvered Shutter □ Key Punched □ Wire Wrapped ■ Saw Cut □ None (Open Hole)									
SCREEN-PERFORATED INTERVALS: From .60									
GRAVEL PACK INTERVALS: From60 ft. to20 ft., From ft. to ft. to ft.									
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other									
Grout Intervals: From									
□ Septic			es		Livestock Pens	s 🗇 Insectio	cide Storage		
☐ Sewer		☐ Lateral Lin☐ Cess Pool			Fuel Storage		oned Water Well		
	ight Sewer L				Fertilizer Stora		Il/Gas Well		
Other (Specify) .No	one							
Direction from well?									
10 FROM	TO	LITHOLO	GIC LOG	FROM	TO I	ITHO. LOG (cont.) or	PLUGGING INTERVALS		
0 3	3	Top soil							
3	13	Brown clay							
13	18	Sand & gravel-small	to med clean coarse						
18	42	Hard gray clay							
42	60	Sand & gravel- small	med clean coarse						
	Notes:								
11 CONTRACTORIO OR LANDONINDRIO CRESTIGIO CONTRACTORIO CO									
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged									
under my jurisdiction and was completed on (mo-day-year) .9-16-1.6									
under the business name of Rosencrantz-Bemis Ent.lnc. Signature Signature									
Mail I white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section,									
		St., Suite 420, Topeka, Kansas		-					
Visit us at http://www.kdheks.gov/waterwell/index.html KSA 82a-1212 Revised 7/10/2015									