

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Barton</u>	<u>NW 1/4 SW 1/4 SE 1/4</u>	<u>28</u>	<u>T 19 S</u>	<u>R 13 EW</u>

Distance and direction from nearest town or city street address of well if located within city?

Great Bend Fuel Station

2 WATER WELL OWNER: <u>City of Great Bend</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>1205 Williams</u>	Application Number:
City, State, ZIP Code: <u>Great Bend, KS. 67530</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>15'6"</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. <u>9'12"</u> ft. 2. . ft. 3. . ft.
	WELL'S STATIC WATER LEVEL <u>9'10"</u> ft. below land surface measured on mo/day/yr <u>9/7/94</u>
	Pump test data: Well water was . ft. after . hours pumping . gpm
	Est. Yield . gpm: Well water was . ft. after . hours pumping . gpm
	Bore Hole Diameter: <u>8 1/2"</u> in. to <u>15'6"</u> ft., and . in. to . ft.
	WELL WATER TO BE USED AS:
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well
	2 Irrigation 4 Industrial 7 Lawn and garden only <u>10</u> Monitoring well 12 Other (Specify below)
	Was a chemical/bacteriological sample submitted to Department? Yes. No <u>X</u> ; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes <u>(No)</u>

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
<u>2 PVC</u>	7 Fiberglass		Threaded <u>X</u>
Blank casing diameter <u>2.375</u> in. to <u>5'</u> ft., Dia in. to ft., Dia in. to ft.			
Casing height above land surface <u>Flush Mount</u> in., weight lbs./ft. Wall thickness or gauge No. <u>SDR-13</u>			<u>sch 40</u>
TYPE OF SCREEN OR PERFORATION MATERIAL:	<u>7 PVC</u>	10 Asbestos-cement	
1 Steel	8 RMP (SR)	11 Other (specify)	
2 Brass	9 ABS	12 None used (open hole)	
3 Stainless steel			
4 Galvanized steel			
5 Fiberglass			
6 Concrete tile			
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
3 Mill slot			
4 Key punched			
SCREEN-PERFORATED INTERVALS: From <u>15'</u> ft. to <u>5'</u> ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From <u>15'6"</u> ft. to <u>4'</u> ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	<u>2</u> Cement grout	<u>3</u> Bentonite	4 Other
Grout Intervals: From <u>4'</u> ft. to <u>2'1/2'</u> ft., From <u>2'1/2'</u> ft. to <u>0'</u> ft., From ft. to ft.				
What is the nearest source of possible contamination:	<u>3</u>	<u>2</u>		
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	<u>11</u> Fuel storage <u>Farm</u>	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	
Direction from well? <u>West South West</u>			How many feet? <u>200'</u>	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>1.25</u>	<u>Asphalt/Concrete</u>			
<u>1.25</u>	<u>3.25</u>	<u>DK Br sandy silty clay, moist, no odor</u>			
<u>3.25</u>	<u>10.0</u>	<u>Br fine grained sand, dry, no odor, well sorted</u>			
<u>10.0</u>	<u>15.50</u>	<u>DK Gray sand & gravel, wet, strong odor subrounded, well graded</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>9-7-94</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>539</u> This Water Well Record was completed on (mo/day/yr) <u>9-12-94</u> under the business name of <u>G. B. Env. Drilling</u> by (signature) <u>James Bieker</u>
--