

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Barton</u>	<u>NE 1/4 NE 1/4 NW 1/4</u>	<u>28</u>	<u>T 19 S</u>	<u>R 13 E</u>

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: <u>CITY OF GREAT BEND</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>Britt Sprague Park, North Main St.</u>	Application Number:
City, State, ZIP Code: <u>GREAT BEND, KS.</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>16.0</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>9.23</u> ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>10</u> Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes <u>No</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>No</u>

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
<u>2</u> PVC	4 ABS	7 Fiberglass	<u>Welded</u>
Blank casing diameter <u>2</u> in. to <u>6.0</u> ft. Dia			<u>Threaded</u>
Casing height above land surface <u>0</u> in., weight lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:	<u>2</u> PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	<u>3</u> Mill slot	9 Drilled holes	
2 Louvered shutter	4 Key punched	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From <u>6.0</u> ft. to <u>16.0</u> ft.			
GRAVEL PACK INTERVALS: From <u>5.0</u> ft. to <u>16.0</u> ft.			

6 GROUT MATERIAL:	1 Neat cement	<u>2</u> Cement grout	<u>3</u> Bentonite	4 Other
Grout Intervals: From <u>0</u> ft. to <u>1.0</u> ft.		From <u>1.0</u> ft. to <u>3.0</u> ft.		From <u>3.0</u> ft. to <u>5.0</u> ft.
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well?				How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>3.0</u>	<u>Topsoil, dark brown organic w/clay</u>			
<u>3.0</u>	<u>6.0</u>	<u>clay, brown, w/silt</u>			
<u>6.0</u>	<u>10.0</u>	<u>sand, fine to med. grained</u>			
<u>10.0</u>	<u>16.0</u>	<u>sand, coarse grained wet at 10'</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>7-14-94</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>438</u> This Water Well Record was completed on (mo/day/yr) <u>7/15/94</u> under the business name of <u>Kansas City Testing Lab, Inc.</u> by (signature) <u>[Signature]</u>
--