

LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: BARTON	NW ¼ NE ¼ NE ¼	32	T 19 S	R 13 E	(W)
Distance and direction from nearest town or city street address of well if located within city?					
200 FT. EAST OF 10TH & MADISON; GREAT BEND, KANSAS					
WATER WELL OWNER: KLEPPER OIL COMPANY, INC.					
R#, St. Address, Box #: 2823 10TH STREET					
City, State, ZIP Code: GREAT BEND, KANSAS 67530					
Board of Agriculture, Division of Water Resources					
Application Number:					
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		DEPTH OF COMPLETED WELL: 17' ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 8.5 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 8.5 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter .in. to .ft., and .in. to .ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No X			
TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded					
Blank casing diameter 2 in. to 7 ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface Flush ft. weight lbs./ft. Wall thickness or gauge No. SCH 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) Sch 40					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 7 Torch cut 9 Drilled holes 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 17' ft. to 7' ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 17' ft. to 5.5 ft. From ft. to ft.					
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout intervals: From 0 ft. to 1 ft. From 5.5 ft. to 3 ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? How many feet?					
FROM TO		LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS	
0 8		BRA SAND CLAY			
8 18		YEL BRA SAND			
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-18-94 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 568A This Water Well Record was completed on (mo/day/yr) 10-23-94					
Under the business name of Hunziker Drilling Co by (signature) David Hunziker					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					