

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: BARTON	NW 1/4 NE 1/4 NE 1/4	32	T 19 S	R 13 EW

Distance and direction from nearest town or city street address of well if located within city?

200 FT. EAST OF 10TH + MADISON: GREAT BEND, KANSAS

2 WATER WELL OWNER: KLEPPER OIL COMPANY, INC.	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 2823 10TH STREET	Application Number:
City, State, ZIP Code: GREAT BEND, KANSAS 67530	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 17' ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 8 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter in. to ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded Threaded X
Blank casing diameter 2 in. to ft., Dia. in. to ft., Dia. in. to ft.			
Casing height above land surface 0 in., weight lbs. ft. Wall thickness or gauge No. Sch 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:	2 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 17' ft. to 7' ft. From ft. to ft. From ft. to ft. From ft. to ft.			
GRAVEL PACK INTERVALS: From 17' ft. to 5.5' ft. From ft. to ft. From ft. to ft. From ft. to ft.			

6 GROUT MATERIAL: 1 Neat cement	2 Cement grout	5.5' Bentonite	4 Other
GROUT INTERVALS: From 0.5 ft. to 0 ft. From 5.5' ft. to 3 ft. From ft. to ft. From ft. to ft.			
What is the nearest source of possible contamination:	7 Pit privy	10 Livestock pens	14 Abandoned water well
1 Septic tank	4 Lateral lines	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	13 Insecticide storage	

Direction from well?	How many feet?
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS	
0 8 BRN Sandy Clay	
8 18 BRN SAND	

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-19-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 568A This Water Well Record was completed on (mo/day/year) 10-23-94 under the business name of HUNZIKER DRILLING CO by (signature) David Hunziker
