

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Barton</u>	<u>SW</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$	<u>34</u>	T <u>19</u> S	R <u>14</u> EW

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER:	<u>Fuller Brush</u>	<u>MW 2A</u>
RR#, St. Address, Box # :	<u>Great Bend Ks 67530</u>	Board of Agriculture, Division of Water Resources
City, State, ZIP Code :		Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>25</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>13.3</u> ft. below land surface measured on mo/day/yr <u>7-31-95</u> Pump test data: Well water was <u>N/A</u> ft. after hours pumping gpm Est. Yield gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter: <u>8 1/4</u> in. to <u>25</u> ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>10</u> Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>✓</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <u>✓</u>

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
<u>2</u> PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter in. to <u>15</u> ft., Dia in. to ft., Dia in. to ft.			Threaded <u>✓</u>
Casing height above land surface <u>24</u> in., weight <u>69</u> lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	<u>3</u> Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS:			
From <u>15</u> ft. to <u>25</u> ft., From ft. to ft.			
GRAVEL PACK INTERVALS:			
From <u>11</u> ft. to <u>25</u> ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	<u>3</u> Bentonite	4 Other
Grout Intervals: From <u>2</u> ft. to <u>11</u> ft., From ft. to ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	<u>16</u> Other (specify below)
Direction from well? <u>SW</u>			How many feet? <u>2150</u>	<u>Dry well - Chem. Source</u>

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>2</u>	<u>Sandy Clay</u>			
<u>2</u>	<u>7</u>	<u>Clay</u>			
<u>7</u>	<u>8.5</u>	<u>Clayey sand</u>			
<u>8.5</u>	<u>12</u>	<u>sand</u>			
<u>12</u>	<u>13.5</u>	<u>Clay</u>			
<u>13.5</u>	<u>35</u>	<u>Gravelly sand</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>10-2-95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>581</u> This Water Well Record was completed on (mo/day/yr) <u>10-26-95</u> under the business name of <u>Layne, Inc.</u> by (signature) <u>Steven R. Mitchell</u>
