

1) LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Barton	SW ¼ SW ¼ NW ¼	36	T 19 S	R 14 E	W
Distance and direction from nearest town or city street address of well if located within city? 2150' FNL, 400' FWL					
2) WATER WELL OWNER: Plating, Inc					
RR#, St. Address, Box # : 8801 W. 6th, West Port Addition			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Great Bend, Kansas 67530			Application Number:		
3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4) DEPTH OF COMPLETED WELL 32 ft. ELEVATION: 999			
1 Mile N W X E S		Depth(s) Groundwater Encountered 1. 19 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL . . . 999 . . . ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was . . NA . . . ft. after . . . hours pumping . . . gpm			
		Est. Yield . . NA . . gpm; Well water was . . . ft. after . . . hours pumping . . . gpm			
		Bore Hole Diameter . . . 8 . . in. to . . 33 . . . ft., and . . . in. to . . . ft.			
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		8 Concrete tile Welded			
(2) PVC 4 ABS		9 Other (specify below) Threaded. ✓			
Blank casing diameter 2 . . . in. to . . 17 . . . ft., Dia . . . in. to . . . ft., Dia . . . in. to . . . ft.					
Casing height above land surface 0 . . . in., weight . . . lbs./ft. Wall thickness or gauge No. . . Sch. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL		(7) PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot (3) Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 17 . . . ft. to . . . 32 . . . ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 15 . . . ft. to . . . 33 . . . ft., From ft. to ft.					
FROM ft. to ft., FROM ft. to ft.					
6) GROUT MATERIAL: 1 Neat cement (2) Cement grout (3) Bentonite 4 Other					
Grout Intervals: From 0 . . . ft. to . . . 13 . . . ft., From . . . 13 . . . ft. to . . . 15 . . . ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
Direction from well?		13 Insecticide storage How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	9	Clay, Black			
9	12	Clay, Dark Brown			
12	15	Sand, Tan			
15	31	Sand, Tan			
31	33	Clay, Yellow			
					MW18 , Flushmount
					Project Name: Plating, Inc.
					GeoCore # 122 , Kejr Science Group # 94-012A
7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1/28/97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 2/18/97 under the business name of GeoCore Services, Inc. by (signature) <i>[Signature]</i>					