


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Barton	N 1/4 C 1/4 NW 1/4	35	T 19 S	R 14 E/W

Distance and direction from nearest town or city street address of well if located within city?

1 1/2 west, 1/4 south of Great Bend, Ks.

2 WATER WELL OWNER: Richard Brining	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: Rt. 1	Application Number: 28,434
City, State, ZIP Code: Great Bend, Ks. 67530	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 103 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 14 ft. below land surface measured on mo/day/yr 6-11-97
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield 1600 gpm: Well water was 44' 10" ft. after 4 hours pumping 1600 gpm
	Bore Hole Diameter 28 in. to 103 ft. and in. to ft.
	WELL WATER TO BE USED AS:
	5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron 8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel 3 RMP (SR)	6 Asbestos-Cement 9 Other (specify below)	Welded
2 PVC 4 ABS	7 Fiberglass	Threaded
Blank casing diameter 16 in. to 56 ft., Dia. 70 to 88 in. to ft., Dia. in. to ft.		
Casing height above land surface 12 in., weight SDR 32.5 lbs./ft. Wall thickness or gauge No.		
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC 10 Asbestos-cement	
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped 8 Saw cut 11 None (open hole)	
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)		
SCREEN-PERFORATED INTERVALS: From 56 ft. to 70 ft., From 83 ft. to 103 ft.		
GRAVEL PACK INTERVALS: From 103 ft. to 20 ft., From ft. to ft.		

6 GROUT MATERIAL:	1 Neat cement 2 Cement grout 3 Bentonite 4 Other	
Grout Intervals: From 20 ft. to 0 ft., From ft. to ft., From ft. to ft.		
What is the nearest source of possible contamination:	10 Livestock pens 14 Abandoned water well	
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)		
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage none		
Direction from well?	How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Top soil			
3	7	Brown & gray clay			
7	27	Sand and gravel clean, coarse, loose			
27	42	Brown clay			
42	47	Blue gray clay			
47	49	Black clay			
49	52	Brown clay			
52	63	Sand and gravel clean, coarse, loose			
63	78	Brown clay			
78	100	Sand and gravel clean, coarse, loose			
100	103	Sand with clay mixed			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-19-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 7-22-97 under the business name of Rosencrantz-Bemis by (signature) Fredia Hodson
