

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number			
County: Barton		SW ¼ SE ¼ SE ¼		34		T 19 S		R 14 E/W			
Distance and direction from nearest town or city street address of well if located within city?											
Approximately 1500' north of water tower at Great Bend Airport											
2 WATER WELL OWNER: City of Great Bend											
RR#, St. Address, Box # : 1209 Williams.					Board of Agriculture, Division of Water Resources						
City, State, ZIP Code : Great Bend, KS 67530					Application Number:						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: 99 ft. ELEVATION: unknown								
			Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.								
			WELL'S STATIC WATER LEVEL 13.35 ft. below land surface measured on mo/day/yr 10-8-97								
			Pump test data: Well water was not ch'd. ft. after hours pumping gpm								
			Est. Yield unknown gpm: Well water was ft. after hours pumping gpm								
			Bore Hole Diameter 5 in. to 100 ft. and in. to ft.								
			WELL WATER TO BE USED AS:								
			5 Public water supply		8 Air conditioning		11 Injection well				
			1 Domestic		3 Feedlot		6 Oil field water supply		9 Dewatering		
			2 Irrigation		4 Industrial		7 Lawn and garden only		10 Monitoring well		
			Was a chemical/bacteriological sample submitted to Department? Yes No ☒ X If yes, mo/day/yr sample was submitted								
			Water Well Disinfected? Yes No ☒ X								
5 TYPE OF BLANK CASING USED:											
1 Steel			3 RMP (SR)		5 Wrought iron		8 Concrete tile		CASING JOINTS: Glued ☒ X Clamped		
2 PVC			4 ABS		6 Asbestos-Cement		9 Other (specify below)		Welded		
					7 Fiberglass				Threaded		
Blank casing diameter 2 in. to 87 ft. Dia in. to ft. Dia in. to ft.											
Casing height above land surface 24 in. weight .70 lbs./ft. Wall thickness or gauge No. 154											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1 Steel			3 Stainless steel		5 Fiberglass		7 PVC		10 Asbestos-cement		
2 Brass			4 Galvanized steel		6 Concrete tile		8 RMP (SR)		11 Other (specify)		
							9 ABS		12 None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:											
1 Continuous slot			3 Mill slot		5 Gauzed wrapped		8 Saw cut		11 None (open hole)		
2 Louvered shutter			4 Key punched		6 Wire wrapped		9 Drilled holes				
					7 Torch cut		10 Other (specify)				
SCREEN-PERFORATED INTERVALS:											
From 87 ft. to 97 ft. From ft. to ft.											
GRAVEL PACK INTERVALS:											
From 72 ft. to 100 ft. From ft. to ft.											
6 GROUT MATERIAL:											
1 Neat cement			2 Cement grout		3 Bentonite		4 Other Benotnite Holeplug				
Grout Intervals: From ft. to ft. From ft. to ft. From 0 ft. to 72 ft.											
What is the nearest source of possible contamination:											
1 Septic tank			4 Lateral lines		7 Pit privy		10 Livestock pens		14 Abandoned water well		
2 Sewer lines			5 Cess pool		8 Sewage lagoon		11 Fuel storage		15 Oil well/Gas well		
3 Watertight sewer lines			6 Seepage pit		9 Feedyard		12 Fertilizer storage		16 Other (specify below)		
							13 Insecticide storage		None known		
Direction from well? How many feet?											
FROM		TO		LITHOLOGIC LOG		FROM		TO		PLUGGING INTERVALS	
0		4		Topsoil							
4		6		Clay, gray							
6		27		Sand and gravel, coarse, medium, fine							
27		28		Clay, yellow and white							
28		36		Sand and gravel, coarse, medium, fine							
36		47		Clay, tan							
47		67		Sand and gravel, coarse, medium, fine							
67		73		Clay, tan							
73		97		Sand and gravel, medium, fine							
97		100		Clay, brown							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-8-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 10-21-97 under the business name of Clarke Well & Equipment, Inc. by (signature) <i>Clarke Well & Equipment, Inc.</i>											