

1 LOCATION OF WATER WELL: Barton		Fraction SE 1/4 NE 1/4 SW 1/4		Section Number 25		Township Number T 19 S		Range Number R 14W EW	
Distance and direction from nearest town or city street address of well if located within city? West edge of Great Bend, Kansas									
2 WATER WELL OWNER: Hiss, Inc.		H-30 Drilling, Inc.		Hiss #3					
RR#, St. Address, Box # : Route 4		251 N. Water, #10		Board of Agriculture, Division of Water Resources					
City, State, ZIP Code : Great Bend, Ks. 67530		Wichita, Ks. 67202		Application Number: T88-623					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 82 ft.		ELEVATION: Unknown					
		Depth(s) Groundwater Encountered 1. 17 ft. 2. ft. 3. ft.		WELL'S STATIC WATER LEVEL 17 ft. below land surface measured on mo/day/yr 11/29/88					
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield 60 gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 8 in. to 82 ft., and in. to ft.							
		WELL WATER TO BE USED AS:		5 Public water supply		8 Air conditioning		11 Injection well	
		1 Domestic		3 Feedlot		6 Oil field water supply		9 Dewatering	
		2 Irrigation		4 Industrial		7 Lawn and garden only		10 Monitoring well	
		Was a chemical/bacteriological sample submitted to Department? Yes No		If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:		5 Wrought iron		8 Concrete tile		CASING JOINTS: Glued Clamped			
1 Steel		3 RMP (SR)		6 Asbestos-Cement		Welded			
2 PVC		4 ABS		7 Fiberglass		Threaded			
Blank casing diameter 5 in. to 62 ft., Dia in. to ft., Dia in. to ft.									
Casing height above land surface 12 in., weight 2.8 lbs./ft. Wall thickness or gauge No. Sch. 40									
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC		10 Asbestos-cement					
1 Steel		3 Stainless steel		5 Fiberglass		8 RMP (SR)		11 Other (specify)	
2 Brass		4 Galvanized steel		6 Concrete tile		9 ABS		12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped		8 Saw cut		11 None (open hole)			
1 Continuous slot		3 Mill slot		6 Wire wrapped		9 Drilled holes			
2 Louvered shutter		4 Key punched		7 Torch cut		10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 62 ft. to 82 ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From 20 ft. to 82 ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement		2 Cement grout		3 Bentonite		4 Other			
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.									
What is the nearest source of possible contamination:		10 Livestock pens		14 Abandoned water well					
1 Septic tank		4 Lateral lines		7 Pit privy		11 Fuel storage		15 Oil well/Gas well	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		12 Fertilizer storage		16 Other (specify below)	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		13 Insecticide storage			
Direction from well? South		How many feet? 60							
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS							
0 15 Clay									
15 25 Sand and gravel									
25 40 Clay									
40 82 Sand and gravel									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/29/88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 186 This Water Well Record was completed on (mo/day/yr) 12/28/88 under the business name of Kelly's Water Well Service by (signature) Kelly's Water Well Service									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.									