


1 LOCATION OF WATER WELL: County: Rush Fraction: NE 1/4 NE 1/4 NE 1/4 Section Number: 14 Township Number: T 19 S Range Number: R 17W EW

Distance and direction from nearest town or city street address of well if located within city?

1/2 S, 1 E of Timken, Kansas

2 WATER WELL OWNER: Richard Smolik RR#, St. Address, Box #: Route 1 City, State, ZIP Code: Timken, Kansas 67582 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 255 ft. ELEVATION: Unknown

Depth(s) Groundwater Encountered: 1. 170 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL: 170 ft. below land surface measured on 6/6/86

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield: 30 gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter: 8 in. to 255 ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded

7 Fiberglass Threaded

Blank casing diameter: 5 in. to 235 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface: 12 in., weight 2.8 lbs./ft. Wall thickness or gauge No. Sch. 40

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 235 ft. to 255 ft. From ft. to ft.

From ft. to ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 10 ft. to 255 ft. From ft. to ft.

From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 10 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? West How many feet? 80

Table with columns FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHOLOGIC LOG

FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG

0 25 Clay

25 185 Shale

185 235 Sand rock