1 LOCATI	ION OF WATE	ER WELL:	Fracti		R WELL REC	OKD FOR		ction Nu	umber		wnship N	lumber	Rano	ge Numbe	r
County: Rush			NE	1/4	SE 1	4 SE	1/4	26			19		1	18	w
Distance ar	nd direction fro				dress of well	f located wi	thin city?			· · ·					
-		·				sh Count	y, Kansa	s							
_	WELL OWN		County	Landi	fill										
1	ddress, Box #			140						Boar	d of Agri	culture, Div	vision of Wa	ater Resou	ırces
	ZIP Code			, KS						Appli	cation N	umber:			
3 AN "X" I	E WELL'S LO N SECTION E	CATON WITH BOX:	H 4 DEP	TH OF C	OMPLETED	WELL	30) ft	FLEV	ATION:					
			Depth(s)	Ground	water Encour	tered 11.5	2	0	ft	2		ft	3		Ç
	N		WELL'S	STATIC	WATER LEV	r=ı 19	9.75 ft	helow	land si	rface m	easured	on molday	/vr 0	9/28/10	Ft. OFFICE
A F	: 		111111111111111111111111111111111111111		test data:										Gom H
			Est Viel		Gpm:										
 -	NW	NE	Bore Hol	e Diame	ter 8.62	In to	, as	0	٠ ٦	f and		Hours	pumping .	'	5 C
Wile W			- WELL W	ATER TO	ter 8.625 O BE USED A 3 Feed lo	ĀS: 5 Pū	blic water s	vlaque		R. and 8 Aii	condition	nina 1	1 Injection	well	Ft. S
¥ W			⁻ 1 C	omestic	3 Feed lo	6 Oil	field water	supply		9 De	ewatering	1	2 Other (S	pecify bel	ow)
	sw	SE		rigation	4 Industria	al 7 Lav	wn and gar	den (da	mestic) 10 N	/lonitorin	g well	M۷	V-1A	
	3W T -	SE - X	Was a ch	nemical/b	oacteriologica					_					vas
†		<u> </u>	Submitte			·		·				ed? Yes		No X	
5 TYPE O	F BLANK SA	SING USED:			5 Wrough	t Iron	8 Conci	rete tile					ed	Clamped	
1 Ste	eel	3 RMP	(SR)		6 Asbesto							Weld			
2 PV		4 ABS	` '		7 Fibergla				-	,			aded	X	
					Ft										
Blank casin	g diameter	2	in. to	18	Dia		ln.	to		ft., Dia			in. to		ft.
Casing heig	ght above land	surface	FLUS	H 1	In., weight _	SC	H 40		.bs./ft.	Wall thic	ckness o	r gauge No).		
TYPE OF S	CREEN OR F	PERFORATION	ON MATER	IAL:			7					estos-ceme			
1 Ste			less steel		5 Fibergla		8	RMP ((SR)		11 Oth	er (specify)			- -
2 Bra			anized stee		6 Concret			ABS				e used (op			
1	R PERFORA					5 Gauze							11 None	(open hol	e)
l .	ntinuous slot		Mill slot			6 Wire w					ed holes				
ł.	uvered shutte					7 Torch o				10 Oth	er (spec	ity)			
SCREEN-P	ERFORATED	INTERVALS			18 ft										
	ND DAOK IN		From		12 ft	. to	20		ft. Fr	om		ft. i	to		^{Ft.} 🗷
SAI	ND PACK INT	ERVALS:			13 ft										
			From		ft	. to			ft. Fr	om		ft.	to		Ft.
GROUT	MATERIAL:	1 Neat	cement	2	Cement grou	t	3 Ber	ntonite	۱ ۰	4 Other					
Grout Interv	als From2	0.5	ft. to	11	Ft. From3	11	Ft.		13	ft	From		ft. to		ft
	nearest source												andoned w		'''
1 Se	ptic tank	·	4 Later	al lines	7	Pit privy				•			well/ Gas		
1	wer lines		5 Cess			Sewage la				er storag		_	her (specify		
3 Wa	atertight sewer	r lines	6 Seep			Feedyard	•			cide stor			ntamina		e
Direction fro	•			-9-		,			many f		-9-				
FROM	то	CODE		LITHOLO	OGIC LOG		FROM	T			PL	UGGING IN	NTERVALS	,	
0	2	S	oil												K
2	8	S	ity Clay		· .										;
8	27		and												
27	30		hale												
30	TD	E	nd of Bo	renole	9			-							
		 									 				
								-							
								-							
											·				
- 100	070715						ļ.,								
	ACTOR'S OR														l l
	on (mo/day/yr				710							-	-		- 1
1	Contractor's L		-		585			Vater W					day/yr)		U
	usiness name				ed Enviro			00 Dec					Johns		
INSTRU	UCTIONS:. Ple	ease IIII in blan Telephone: 0:	ks and circle	the corre	ct answers. S	ena three co	pies to Kans	sas Depa	artment	oī Health	and En	ronmen	reau of Wat	er, Topeka	,