
USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215



County	Township name	Fraction			on number		Town number	Range number
1 Location of well: Rush		SES	SW	L ,	35	•	195	19 W
Distance and direction from nearest town	or city: 85 2	12 E	3 Owner	of well	:	.00	195 UIS Hag	erman
Street address of well location if in city:			Addre	ess:	N	el	KOMA , K	s.
Locate with "X" in section below:	Sketch map:	- 100 -	<u>. </u>		-			Date of completion 8-8-
N N	1						Wall diameter 💇 in	1
	NO SPA	ge, here i de la desta desta de la composición del la composición del composición de la composición de la composición del composición del composición de la composición del composición del composición del composición del composición del composición del composición	. 	_ K	mark page.	5,	Cable tool X Rotary Hollow rod Detted	☐ Driven ☐ Dug ☐ Bored ☐ Reverse rotary
	A State of the Sta	e prof lagrangia propaga.	appendent out of	nia nambrima	a emperajore ma	. 82	Use: Domestic Publ	ic supply Industry
w	. ε. ∰	and the second sequences and		7 4 5	्द 🔏	·, · ic	Irrigation Air	conditioning Commercial
	velij		er na	a Ei r	nd 7 1	1 19 20	Casing: Material DVC	Height: above below
Ky are uniferral	3.	akt maturet type talle om mer Linear	` Yesi	tes 2	.14 3	64a	Needed Welded	Surface 12 in.
S	vd 3. 2.	and marketings on the district of			4 S	100	Diam. In. to 36-5t. depth	!Weight lbs./ft !Drive shoe? Yes XNo
2 (quality suring a sum a sur holder of the sub-	Type and color of material	A	P. Address Segrega a.p. and a	From	To		in. to ft. depth	
					A	- 8°	Screen: Manufacturer	PI
7	SAND ROO	dy		0	323		Manufacturer Type PVC Slot/gauze Set between 3455 ft. and	Dia. 3-"
	SAND ROO	oK		325	365	-	Slot/gauze Set between 34452 ft. and	Length
							Fittings:	- 3/./"
	-					9	Static water level:	
						<u> </u>	240t. below land surfa	ce Date <u>8-8-75</u>
							Pumping level below land su ft. after hr	
						Ι.	ft. after hr	s. pumping g.p.m.
							Estimated moximum yield — Water sample submitted:	20 g.p.m.
								te
							Well head completion:	12
							Pitless adapter Well grouted? XYYes	Inches above grade
							Neat cement Benton	nite
							Depth: From ft. to	5003
							Nearest source of possible of the contraction —	Type Tank
							Well disinfected upon comp	
							Pump: Manufacturer's name	Not installed
							Model number	tt capacity a m.n.
					 		Туре:	
						1	Submersible Jet	Turbine Reciprocating
	(use a second sheet if needed)					Certrifugal	Other
16 Remarks: elevation							Water well contractor's cert This well was drilled under r	i i
	75	75)				i .	report is true to the best of	· · .
Topography:							Kelly S War	1 license No
Slope						•	Address Address	Treat Bend
Valley ∪pland						'	Authorized repres	entative Date 8 - 15

Forward the white, blue and pink copies to the Kansas State Dept. Of Health.

Form WWC-5