

1 LOCATION OF WATER WELL: Fraction <u>Ne 1/4 NW 1/4 NW 1/4</u> Section Number <u>29</u> Township Number <u>T 19 S</u> Range Number <u>R 2 E</u>
---

Distance and direction from nearest town or city street address of well if located within city?


1 1/2 W Galva2 WATER WELL OWNER: James CoffeyRR#, St. Address, Box # : 1937 E Hwy 56City, State, ZIP Code : McPherson, KS 67449

Board of Agriculture, Division of Water Resources

Application Number:

3 LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL 0.5 ft. ELEVATION: 4-29-05

AN "X" IN SECTION BOX:

Depth(s) Groundwater Encountered 12 ft. 2 40 ft. 3 4-29-05 ft.WELL'S STATIC WATER LEVEL 12 ft. below land surface measured on mo/day/yrPump test data: Well water was 4-5 ft. after 4-5 hours pumping 4-5 gpmEst. Yield 4-5 gpm: Well water was 4-5 ft. after 4-5 hours pumping 4-5 gpm

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Domestic (lawn &amp; garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded

2 PVC 4 ABS 7 Fiberglass Threaded

Blank casing diameter 5 in. to 32 ft. Dia 32 in. to 32 ft. Dia 32 in. to 32 ft.Casing height above land surface 12 in., weight 12.55/60 lbs./ft. Wall thickness or gauge No. 214

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-Cement

1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify)

2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) 32 ft.SCREEN-PERFORATED INTERVALS: From 32 ft. to 52 ft. From 32 ft. to 52 ft.GRAVEL PACK INTERVALS: From 20 ft. to 65 ft. From 20 ft. to 65 ft.7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-29-05 and this record is true to the best of my knowledge and belief. KansasWater Well Contractor's Licence No 180 This Water Well Record was completed on (mo/day/yr) 5-1-05under the business name of Backhus Drilling by (signature) Paul H. Backhus

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.