


1 LOCATION OF WATER WELL: Fraction SE 1/4 SE 1/4 SE 1/4 Section Number 2 Township Number T 19 S Range Number R 2 NW

Distance and direction from nearest town or city street address of well if located within city?

2 1/2 m. N. + 2 m. EAST OF GALVA, KS

2 WATER WELL OWNER: MYRTLE JOHNSON Board of Agriculture, Division of Water Resources
 RR#, St. Address, Box #: 96 REALTY EXCHANGE BOX 442 Application Number:
 City, State, ZIP Code: McPHERSON, KS 67460

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 27 ft. ELEVATION: 25 ft.
 Depth(s) Groundwater Encountered 1. 25 ft. 2. 25 ft. 3. 25 ft.
 WELL'S STATIC WATER LEVEL 25 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 25 ft. after 25 hours pumping 25 gpm
 Est. Yield 25 gpm: Well water was 25 ft. after 25 hours pumping 25 gpm
 Bore Hole Diameter 60 in. to 60 ft., and 60 in. to 60 ft.
 WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below)
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes NA No NA; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes NA No NA

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued NA Clamped NA
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) HAND DUG Welded NA
 7 Fiberglass Threaded NA
 Blank casing diameter 40 in. to 40 ft., Dia. 40 in. to 40 ft., Dia. 40 in. to 40 ft.
 Casing height above land surface 6 in., weight 6 lbs./ft. Wall thickness or gauge No. 6
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) NA
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) NA
 7 Torch cut
 SCREEN-PERFORATED INTERVALS: From 20 ft. to 14 ft., From 20 ft. to 14 ft., From 20 ft. to 14 ft.
 GRAVEL PACK INTERVALS: From 20 ft. to 14 ft., From 20 ft. to 14 ft., From 20 ft. to 14 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 20 ft. to 14 ft., From 20 ft. to 14 ft., From 20 ft. to 14 ft.
 What is the nearest source of possible contamination:
☒ 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? NORTH How many feet? 100

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
		<u>Plugged HAND DUG WELL</u>			
<u>27</u>	<u>20</u>	<u>Chlorinated SAND + GRAVEL</u>			
<u>20</u>	<u>14</u>	<u>BENTONITE Hole Plug</u>			
<u>14</u>	<u>4</u>	<u>SAND + GRAVEL</u>			
<u>4</u>	<u>0</u>	<u>Top Soil</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or ☒ (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-24-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 1-27-92 under the business name of PETERSON Irrigation by (signature) Mike Peterson