

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County McPherson	Fraction NW 1/4 NW 1/4 SE 1/4	Section number 10	Township number T 19 S	Range number R 2 W E/W
2. Distance and direction from nearest town or city: 2 N of Galva Street address of well location if in city: 1 East 1/2 N West in field		3. Owner of well: R.R. or street: Alfred D. Koehn City, state, zip code: Box 89, R. 2, Galva, Kansas 67443				
4. Locate with "X" in section below: N W E S 1 Mile Sketch map: 		6. Bore hole dia. 6" in. Completion date 9-25-79 Well depth 72 ft.				
5. Type and color of material		From	To	7. <input type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary		
Top Soil		0	3	8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input checked="" type="checkbox"/> Oil field water <input type="checkbox"/> Other		
Clay		3	30	9. Casing: Material <input type="checkbox"/> Height: Above or below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 18 in. RMP <input type="checkbox"/> PVC <input checked="" type="checkbox"/> Weight 120 lbs./ft. Dia. 3 in. to 0 ft. depth Wall Thickness: inches or Dia. 3 in. to 32 ft. depth gauge No. 216		
Equis Sand		30	38	10. Screen: Manufacturer's name Certain Teed Type Screened Dia. 3 Slot/gauze 1/16 Length 20 Set between 32 ft. and 72 ft. ft. and 72 ft. Gravel pack? Yes Size range of material 4 x 24		
Equis Sand With Clay		38	45	11. Static water level: 24 ft. below land surface Date 9-25-79 mo./day/yr.		
Clay		45	57	12. Pumping level below land surfaces: 30 ft. after 1 hrs. pumping 75 g.p.m. ft. after 1 hrs. pumping 75 g.p.m. Estimated maximum yield 100 g.p.m.		
Equis Sand		57	60	13. Water sample submitted: mo./day/yr. <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date		
Equis Sand		60	72	14. Well head completion: <input type="checkbox"/> Pitless adapter 18 Inches above grade		
Shale		72	---	15. Well grouted? Yes With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 6 ft. to 10 ft.		
(Use a second sheet if needed)				16. Nearest source of possible contamination: ft. Direction North Type None Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		
				17. Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name Model number HP Volts Length of drop pipe ft. capacity g.p.m. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
18. Elevation:		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Rosencrantz-Bemis Ent. Inc. 134 Business name License No. Address 1211 W. 4th. Hutchinson, Kansas Signed Mike Rows Date 10-15-79 Authorized representative		