

1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 SW 1/4 Section Number 22 Township Number 19 S Range Number 2 E

Distance and direction from nearest town or city street address of well if located within city?
In Galva 203 E 5th

2 WATER WELL OWNER: Paul Koehn
RR#, St. Address, Box #: 203 E 5th
City, State, ZIP Code: Galva KS 67443

Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 32 ft. ELEVATION: 23- ft.

Depth(s) Groundwater Encountered 1. 16 ft. 2. 23- ft. 3. 10-25-29 ft.

WELL'S STATIC WATER LEVEL 16 ft. below land surface measured on mo/day/yr 10-25-29

Pump test data: Well water was 20 gpm ft. after 32 hours pumping gpm

Est. Yield 20 gpm Well water was 32 ft. after 32 hours pumping gpm

Bore Hole Diameter 9 in. to 32 ft., and 32 in. to 32 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
Blank casing diameter 5 in. to 22 ft. Dia 22 in. to 22 ft. Dia 22 in. to 22 ft. Dia
Casing height above land surface 12 in. weight 12 lbs./ft. Wall thickness or gauge No. 2.14

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 22 ft. to 32 ft. From 22 ft. to 32 ft.
GRAVEL PACK INTERVALS: From 10 ft. to 32 ft. From 10 ft. to 32 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 10 ft. From 0 ft. to 10 ft. From 0 ft. to 10 ft. From 0 ft. to 10 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage

Direction from well? E How many feet? 40

FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG
0 14 Clay
14 32 medium sand

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-26-24 and this record is true to the best of my knowledge and belief Kansas
Water Well Contractor's License No. 120 This Water Well Record was completed on (mo/day/yr) 10-26-24
under the business name of Backhus Drilling by (signature) Paul Koehn

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.