WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL:	Fraction	Section Number Township No. Range Number
County: McPherson	1/4 NE1/4 SW 1/4 NE1/4	2/ T 19 S R 2 □E 12 W
Street/Rural Address of Well Location;	if unknown, distance & direction	Global Positioning System (GPS) information:
from nearest town or intersection: If at	owner's address, check here 🗹.	Latitude: 38.38.66.4 (in decimal degrees)
	·	Longitude:
		Elevation:
2 WATER WELL OWNER: Key	all lines	- <u>Datum</u> : ☐ WGS 84, ☑ NAD 83, ☐ NAD 27
	w John 57	Collection Method:  GPS unit (Make/Model:)
City, State, ZIP Code :	W JOHA 37	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey
Gal	'va, KS 67433	Est. Accuracy: $\square$ <3 m, $\bowtie$ 3-5 m, $\square$ 5-15 m, $\square$ >15 m
3 LOCATE WELL		
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 4.8		
SECTION BOX: Depth(s) Ground	lwater Encountered (1)	ft. (2) ft. (3) ft.
N WELL'S STAT	WELL 5 5 TATIC WATER ELVEL	
Pump	test data: Well water was3.	ft. afterft. aon hours pumping3.5
EST. YIELDgpm. Well water wasft. afterhours pumpinggpm  Well water wasft., andin. toft.		
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well  SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)		
SW -   SE -     Domestic   Feedlot   Oli field water supply   Dewatering   Other (specify below)		
Was a chemical/bacteriological sample submitted to Department? Yes No		
S If yes, mo/day/yr sample was submitted		
1 mile  Water well disinfected?		
5 TYPE OF CASING USED:  Steel  PVC Other		
CASING JOINTS: 🔀 Glued 🗌 Clamped 🔲 Welded 🔲 Threaded		
Casing diameter		
Casing height above land surface. 12. in., Weight 2 3.5. lbs./ft., Wall thickness or gauge No 16.0.		
TYPE OF SCREEN OR PERFORATION MATERIAL:		
☐ Steel ☐ Stainless Steel          ☐ Other (Specify)		
Brass Galvanized Steel None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:		
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)		
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)  SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft.		
From ft. to ft., From ft. to ft.		
GRAVEL PACK INTERVALS: From 23 ft. to 52 ft., From ft. to ft.		
From ft to ft From ft to ft		
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other		
Grout Intervals: From		
What is the nearest source of possible contamination:		
	nes Pit privy Livestock	
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well		
Watertight sewer lines Seepage p		torage  Oil well/gas well from well
Direction from well		TO LITHO. LOG (cont.) or PLUGGING INTERVALS
	TROWI	ETTTO, LOG (COIII.) OF I LOGOTING INTERVALS
10 16 Br Clay		
16 29 L. Gr C/ac		
19 48 F-C Sand		
48 52 Rocky Br + 6	- Cla	
70 Ja Rockly BF F S	-r ciag	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, ☐ reconstructed, or ☐ plugged		
under my jurisdiction and was completed on (mo/day/year) 6.7.8.7/ and this record is true to the best of my knowledge and belief.		
Kansas Water Well Contractor's License No, This Water Well Record was completed on (mo/day/year)		
under the business name of	r Drilling	by (signature) hallo
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS PRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies		
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at		
http://www.kdheks.gov/waterwell/index.html.		
KSA 82a-1212		