


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Ness	Fraction NW 1/4 NW 1/4 NW 1/4	Section number 34	Township number T 19 S R 21 E	Range number 21 E
Distance and direction from nearest town or city: Street address of well location if in city:			3. Owner of well: R.R. or street: City, state, zip code:			
5.5 mi S 3 E of Bazine			Ron Schaben Bazine, Kansas 67516			
4. Locate with "X" in section below: Sketch map:			6. Bore hole dia. 9 7/8 in. Completion date 9-09-76 Well depth 485 ft.			
			7. <input type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary			
5. Type and color of material			8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other			
Top soil			Casing: Material PVC Height: Above or below 12 in. Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input checked="" type="checkbox"/> Weight 291 lbs./ft. 100 Dia. 5 in. to 5 ft. depth Wall Thickness: inches or Dia. 5 in. to 5 ft. depth gage No. 265			
Tan clay			10. Screen: Manufacturer's name Jess & Lowell Type PVC Dio. 5 in. Slot/gauze 1/8" Length 40' Set between 445 ft. and 485 ft. ft. and 485 ft.			
Yellow clay			Gravel pack yes Size range of material 3/16"			
Black shale			11. Static water level: 173 ft. below land surface Date 8/20/76 mo./day/yr.			
Black shale & soft red clay			12. Pumping level below land surfaces: ft. after 4 hrs. pumping 2 g.p.m. ft. after 4 hrs. pumping 2 g.p.m. Estimated maximum yield 2 g.p.m.			
Sandstone & clay (red & black)			13. Water sample submitted: yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date 8/20/76 mo./day/yr.			
Sandstone			14. Well head completion: <input checked="" type="checkbox"/> Pitless unit <input type="checkbox"/> unit inches above grade			
			15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 4 ft. to 14 ft.			
			Nearest source of possible contamination: ft. 300 Direction West Type old well Well disinfected upon completion? <input type="checkbox"/> Yes <input type="checkbox"/> No			
			17. Pump: Manufacturer's name Aermotor Model number SD12 19 HP 1/2 2 Volts 220 Length of drop pipe 210 ft. capacity 20 g.p.m. Type: <input checked="" type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other			
(Use a second sheet if needed)						
18. Elevation:		19. Remarks:				
Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Friesen Windmill 252 Business name License No. Address Meade, Kansas 67864 Signed Friesen Date 9-22-76 Authorized representative				

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5