

CORRECTION(S) TO WATER WELL RECORD (WWC-5)
(to rectify lacking or incorrect information)

County: Ness

Location listed as:

Location changed to:

Section-Township-Range: 19-22S-28W

28-19S-24W

Fraction ($\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$): SE SE SE

SE SE SE

Other changes: Initial statements: _____

Changed to: _____

Comments: _____

verification method: Written & legal descriptions, county ownership directory, position on plat map, and mapping tool & aerial photos on KGS website. initials: DRJ date: 2/6/2009

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726
to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WELL: Fraction Section Number Township Number Range Number
COUNTY: NESS SE 1/4 SE 1/4 SE 1/4 19 T 22 S R 28 W

Distance and direction from nearest town or city street address of well if located within city?
FROM NESS - 6 SOUTH ON HIGHWAY 283 - 4 WEST ON ROAD 70

2 WATER WELL OWNER: BAIN, CRAIG
RR#, St. Address, Box #: 403 S. SCHOOL Board of Agriculture, Division of Water Resources
City, State, ZIP code: NESS CITY, KS 67560- Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N				
	NW		NE	
W				E
	SW		SE	
				X

4 DEPTH OF COMPLETED WELL 525 ELEVATION: 0
Depth(s) Groundwater Encountered 1. 0 ft. 2. 0 ft. 3. 0 ft.
WELL'S STATIC WATER LEVEL 152 ft. below land surface measured on mo/day/yr 10/21/08
Pump test data: Well water was 0 ft. after 0 hours pumping 0 gpm
Estimated Yield 45 gpm: Well water was 0 ft. after 0 hours pumping 0 gpm
Bore Hole Diameter 9 in. to 525 ft., and in. to 0 ft.
WELL WATER TO BE USED AS: DOMESTIC
Was a chemical/bacteriological sample submitted to department? No ;
If yes, mo/day/yr sample was submitted Water well disinfected? Yes

5 TYPE OF BLANK CASING USED: CERTA LOC CASIN CASING JOINTS: CERTA-LOC
Blank casing diameter 5 in. to 525 ft., Dia in. to 0 ft., Dia in. to 0 ft.
Casing height above land surface 12 in., weight 200 lbs/ft. Wall thickness or gauge No. 21-17
TYPE OF SCREEN OR PERFORATION MATERIAL: PVC
SCREEN OR PERFORATION OPENINGS ARE: SAW CUT

SCREEN PERFORATED INTERVALS: From 420 ft. to 520 ft., From 0 ft. to 0 ft.
From 0 ft. to 0 ft., From 0 ft. to 0 ft.
GRAVEL PACK INTERVALS: From 25 ft. to 80 ft., From 0 ft. to 0 ft.
From 90 ft. to 525 ft., From 0 ft. to 0 ft.

6 GROUT MATERIAL BENTONITE
Grout Intervals: From 5 ft. to 25 ft., From 80 ft. to 90 ft., From 0 ft. to 0 ft.
What is the nearest source of possible contamination: NONE
Direction from well? How many feet? 0

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	20	01 TOPSOIL 32 TAN CLAY			
20	40	32 TAN CLAY 02 FINE SAND			
40	50	10 FINE-MEDSAND			
50	240	07 BLUE SHALE 24 THINROCLAYER			
240	280	36 BLUE CLAY			
280	300	16 GRAY CLAY 29 SANDSTONE 19 LAYERS			
300	360	16 GRAY CLAY			
360	500	29 SANDSTONE			
500	540	29 SANDSTONE 16 GRAY CLAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 11/20/08 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) 11/20/08 under the business name of JOE'S WELL SERVICE, INC. by (signature) *Joe's Well Service*