		WAT	ER WELL RECORD Fo	orm WWC-5	KSA 82a			
LOCATION OF WA		Fraction	. N 16) A 2		n Number	Township Nu		Range Number
unty: Vess	from nearest tou		address of well if located v	within city?	<u> </u>	<u> </u>	S	I R 26 W
- 1 -	~ ·			within City:				
	South	OF	eeler, 15.					
WATER WELL ON	NEH: ///	n Cons	teuction .			Daniel of A		Nicialan af Matau Danassus
#, St. Address, Bo							-	Division of Water Resource
, State, ZIP Code		sborg,		7 9		Application	Number:	36-834
OCATE WELL'S L N "X" IN SECTION			COMPLETED WELL					
	<u> </u>		ndwater Encountered 1					
^ !	/ ! i		C WATER LEVEL / /.					
NW	NE		mp test data: Well water v					
1		Est. Yield	3 O . gpm: Well water v	was	ft. a	fter	hours pur	mping gpm
w - !	-		meter $f 8$ in. to					toft.
·" !	!]	WELL WATER	TO BE USED AS: 5	Public water :	supply	8 Air conditioning	11	Injection well
sw	SF	1 Domesti				9 Dewatering		Other (Specify below)
1 1	1	2 Irrigation						
t		Was a chemica	l/bacteriological sample sub	omitted to Dep	artment? Ye	sNo	; If yes,	mo/day/yr sample was sub
	5	mitted			Wa	ter Well Disinfected	i? Yes	No
TYPE OF BLANK (CASING USED:		5 Wrought iron	8 Concrete	tile	CASING JOI	NTS: Gluec	1 . 1
1 Steel	3 RMP (SF	₹)	6 Asbestos-Cement	9 Other (sp	pecify below	v)	Welde	ed
2 PVC	4 ABS		7 Fiberglass				_	ided
			O ft., Dia					
sing height above la	and surface	ح.١٠	in., weight	4. 4. 1	lbs./	ft. Wall thickness o	r gauge No	5
PE OF SCREEN O	R PERFORATION	N MATERIAL:	1	7 PVC		10 Asba	stos-ceme	nt
1 Steel	3 Stainless	steel	5 Fiberglass	8 RMP	(SR)	11 Othe	er (specify)	
2 Brass	4 Galvaniz	ed steel	6 Concrete tile	9 ABS		12 Non	e used (op	en hole)
REEN OR PERFO	RATION OPENING	GS ARE:	5 Gauzed	wrapped		8 Saw cut		11 None (open hole)
1 Continuous slo	ot <u>3 M</u> i	ill slot	6 Wire wra	apped		9 Drilled holes		
2 Louvered shut	ter 4 Ke	ey punched	7 Torch c	ut		10 Other (specify)	
REEN-PERFORAT	ED INTERVALS:	From	ft. to	<i>₹8</i>	ft., Fro	n	ft. to	o
		From	ft. to	<u></u>	ft., Froi	n	ft. to	o
GRAVEL PA	CK INTERVALS:	From	 ft. to	3&	ft., Fro	n	ft. to	o
		From	ft. to		ft., Fro	n	ft. to	o ft.
GROUT MATERIAL	L: ALAGA	6/4/4 t	2 Cement grout	(3 Bentonit	4	Other		
out Intervals: Fro			ft., From	ft. to	<i></i>	ft., From	. 	ft. to
at is the nearest so	ource of possible	contamination:			10 Lives	tock pens	14 AI	bandoned water well
1 Septic tank	4 Latera	al lines	7 Pit privy		11 Fuel	storage	15 O	il well/Gas well
2 Sewer lines	5 Cess	pool	8 Sewage lagoor	n		zer storage	16 O	ther (specify below)
3 Watertight sev	ver lines 6 Seep	•	9 Feedyard			ticide storage		
ection from well?	None w	- / /	t mi.		How ma	_		
ROM TO		LITHOLOGIC	CLOG	FROM	TO	4	LITHOLOG	IC LOG
04	Top Soi	· /						
4 11	BROWN	SAND	4 Clay.					
11 16	Coarse	SAND 1	Limestone.					
16 24	Brown C	lau +L	mestone					
24 37			+ Lime stone					
37 38	GRAY St							
	7							

		NO OFFI	TION TE:	(4)				
		TS CERTIFICA	TION: This water well was					
npleted on (mo/day	-	··· ; #					st of my kn	owledge and belief. Kansas
ter Well Contractor		TO	This Water Well	Record was		~~~	19.5	7° 7
ler the business na	me of Get	erson a	Wightion	BB/4/E : :	by (signa		re /	recess
			ISE PRESS FIRMLY and I					
ee copies to Kansas VNER and retain o			nment, Division of Environm	ent, Environme	əntai G000(ју зеспоп, горека,	NO 00020.	Send one to WATER WELL
	juu. 100010							