	WATER WE	LL RECORD	Form WW	C-5 KSA 82	2a-1212		
LOCATION OF WATER WELL:	Fraction			Section Numbe	r Township Number	Range Number	
County: McPherson		SW 1/4 N		21	јт 19 s	R 3 E(W)	
Distance and direction from nearest town	or city street address	of well if locati	ed within cit	y?			
1340 North Main	7 V . T						
WATER WELL OWNER: Coasta						13	
	enway Plaza				•	Division of Water Resources	
	on, TX 77046				Application Number:		
LOCATE WELL'S LOCATION WITH 4 AN "X" IN SECTION BOX:	DEPTH OF COMPL	ETED WELL	95	ft. ELEV	ATION:1497.98		
N D					2 ft.		
ī ! ! w					urface measured on mo/day/y		
NW NF	Pump test	data: Well wat	er was	ft.	after hours p	umping gpm	
					after hours p		
w X 1 E B<	ore Hole Diameter	. , 8. ,in. to) <i></i> .		and	n. to , . , . , . , . , . , . , .	
E W	ELL WATER TO BE	USED AS:		ater supply		Injection well	
- SW SE	1 Domestic	3 Feedlot .	6 Oil field	water supply	9 Dewatering 12	Other (Specify below)	
		4 Industrial	7 Lawn ar	d garden only	10 Monitoring well		
	las a chemical/bacteri	ological sample	submitted to	Department?	resNoX if yes	s, mo/day/yr sample was sub	
<u> </u>	itted			w	ater Well Disinfected? Yes	No X	
TYPE OF BLANK CASING USED:	5 Wr	rought iron	8 Cor	ncrete tile	CASING JOINTS: Glue	ed Clamped	
1 Steel 3 RMP (SR)	6 As	bestos-Cement		er (specify belo	,	ded	
2 PVC 4 ABS		erglass			Thre		
Blank casing diameter 2 in.	. to 70	ft., Dia	in.	to	ft., Dia	in. to ft.	
Casing height above land surface	-,23in., w	eight		lbs	ft. Wall thickness or gauge !	No	
TYPE OF SCREEN OR PERFORATION N	MATERIAL:		\bigcirc	PVC	10 Asbestos-cem	ent	
1 Steel 3 Stainless st	teel 5 Fit	erglass	8	RMP (SR)	11 Other (specify	')	
2 Brass 4 Galvanized	steel 6 Co	ncrete tile		ABS	12 None used (o	pen hole)	
SCREEN OR PERFORATION OPENINGS	ARE:	5 Gauz	zed wrapped	!	8 Saw cut	11 None (open hole)	
1 Continuous slot 3Mill s	slot	6 Wire	wrapped		9 Drilled holes		
2 Louvered shutter 4 Key	punched	7 Torci	h cut		10 Other (specify)		
SCREEN-PERFORATED INTERVALS:	From 70	ft. to .	95	ft., Fro	om ft.	toft.	
	From	ft. to .		ft Fro	om ft.	toft.	
GRAVEL PACK INTERVALS:	From 68	ft. to .	95	ft., Fro	om ft.	toft.	
	From	ft. to		ft., Fro	om ft.	to ft.	
GROUT MATERIAL: 1 Neat cerr	nent 🗷 🗷 Cerr	nent grout	(3) ∃a	ntonite 4	Other		
Grout Intervals: From 0 ft.	to 6.8 f	t., From	<i>.</i> f	. to	ft., From	ft. toft.	
What is the nearest source of possible cor						Abandoned water well	
1 Septic tank 4 Lateral I	ines	7 Pit privy		(11) Fuel	storage 15 0	Oil well/Gas well	
2 Sewer lines 5 Cess pool		8 Sewage lagoon			12 Fertilizer storage 16 Other (specify below)		
3 Watertight sewer lines 6 Seepage	e pit	9 Feedyard		13 inse	cticide storage		
Direction from well? South	west			How ma	any feet?		
FROM TO	LITHOLOGIC LOG		FRCM	ТО	PLUGGING	INTERVALS	
			0	65	Bentonite		
			65	95	Sand		
CONTRACTOR'S OR LANDOWNER'S	CERTIFICATION: TI	nis water well w	/as (1) cocc	tructed (2) rec	onstructed or Chalunged up	der my jurisdiction and was	
ompleted on (mo/day/year)	2/95				onstructed, or an plugged directly or		
Vater Well Contractor's License No					0/10	/95	
nder the business name of	GeoCore Serv			was completed by (signa	on (morday)		
						conies to Kansas Department	
INSTRUCTIONS: Use typewriter or ball point pen- of Health and Environment, Bureau of Water, Top	река. Kansas 66620-0001.	Telephone: 913-296-	5545. Send one	to WATER WELL (DWNER and retain one for your record	ds.	