

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: McPherson		SW ¼ SW ¼ NW ¼		21		T 19 S		R 3 E/W	
Distance and direction from nearest town or city street address of well if located within city?									
1340 North Main									
2 WATER WELL OWNER: Coastal Mart Inc.									
RR#, St. Address, Box # : 9 Greenway Plaza						Board of Agriculture, Division of Water Resources			
City, State, ZIP Code : Houston, TX 77046						Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:				4 DEPTH OF COMPLETED WELL: 95 ft. ELEVATION: 1498.97					
				Depth(s) Groundwater Encountered 1. 81 ft. 2. ft. 3. ft.					
				WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr					
				Pump test data: Well water was ft. after hours pumping gpm					
				Est. Yield gpm: Well water was ft. after hours pumping gpm					
				Bore Hole Diameter 8 in. to ft. and in. to ft.					
WELL WATER TO BE USED AS:				5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted									
Water Well Disinfected? Yes No X									
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X Threaded.									
Blank casing diameter 2 in. to 70 ft. Dia in. to ft. Dia in. to ft.									
Casing height above land surface -40 in. weight lbs. ft. Wall thickness or gauge No.									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 70 ft. to 95 ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 68 ft. to 95 ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 0 ft. to 68 ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage									
Direction from well? Southwest How many feet?									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 65 Bentonite									
65 95 Sand									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/22/95 and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 9/18/95									
under the business name of GeoCore Services, Inc. by (signature) Dale Rolf									