


1 LOCATION OF WATER WELL: County: <u>McPherson</u>		Fraction <u>CSL</u> $\frac{1}{4}$ <u>SE</u> $\frac{1}{4}$ <u>SW</u> $\frac{1}{4}$	Section Number <u>23</u>	Township Number T <u>19</u> S	Range Number R <u>3</u> E <u>W</u>
Distance and direction from nearest town or city street address of well if located within city? <u>2201 E. Kansas Ave.</u> <span style="float: right;"><u>AS-12</u></span>					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Fina Oil & Chemical P O Box 2159 Dallas Texas 75221 Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>53.5</u> ft. ELEVATION: <u>53.5</u> ft.			
		Depth(s) Groundwater Encountered <u>30</u> ft. 2. <u>53.5</u> ft. 3. <u>53.5</u> ft. WELL'S STATIC WATER LEVEL <u>30</u> ft. below land surface measured on mo/day/yr Pump test data: Well water was <u>8</u> gpm. Well water was <u>53.5</u> ft. after <u>8</u> hours pumping <u>8</u> gpm. Est. Yield <u>8</u> gpm. Well water was <u>53.5</u> ft. after <u>8</u> hours pumping <u>8</u> gpm. Bore Hole Diameter <u>8</u> in. to <u>53.5</u> ft. and <u>53.5</u> in. to <u>53.5</u> ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well <u>Aquifer Spurge</u> Was a chemical/bacteriological sample submitted to Department? Yes <u>No</u> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>No</u>			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued <u>Clamped</u>			
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded <u>Threaded</u>		Blank casing diameter <u>2</u> in. to <u>50.5</u> ft. Dia <u>6.9</u> in. to <u>53.5</u> ft. Dia <u>53.5</u> in. to <u>53.5</u> ft. Casing height above land surface <u>0</u> in. weight <u>6.9</u> lbs./ft. Wall thickness or gauge No. <u>53.5</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) <u>53.5</u> 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) <u>53.5</u>			
SCREEN-PERFORATED INTERVALS:		From <u>50.5</u> ft. to <u>53.5</u> ft. From <u>53.5</u> ft. to <u>53.5</u> ft. From <u>48</u> ft. to <u>53.5</u> ft. From <u>53.5</u> ft. to <u>53.5</u> ft.			
GRAVEL PACK INTERVALS:		From <u>48</u> ft. to <u>53.5</u> ft. From <u>53.5</u> ft. to <u>53.5</u> ft.			
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other <u>53.5</u>			
Grout Intervals: From <u>48</u> ft. to <u>53.5</u> ft. From <u>53.5</u> ft. to <u>53.5</u> ft.		What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? <u>Gas Station</u> How many feet? <u>&lt; 100'</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>23</u>	<u>Silty sandy clay</u>			
<u>23</u>	<u>40</u>	<u>Sand</u>			
<u>40</u>	<u>53</u>	<u>Clay</u>			
		<u>Shale</u>			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>10-5-95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>591</u> This Water Well Record was completed on (mo/day/year) <u>10-5-95</u> under the business name of <u>Loaym, Inc.</u> <u>Wichita</u> by (signature) <u>Blue Mitchell</u>					