


1 LOCATION OF WATER WELL: County: McPherson Fraction: NW 1/4 NW 1/4 SW 1/4 Section Number: 29 Township Number: T 19 S Range Number: R 3 EW

Distance and direction from nearest town or city street address of well if located within city?
1035 W Kansas, McPherson

2 WATER WELL OWNER: Coastal Murr Inc
RR#, St. Address, Box #: 9 Greenway Plaza Board of Agriculture, Division of Water Resources
City, State, ZIP Code: Houston TX 77046 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 88.13 ft. ELEVATION: 1486.84
Depth(s) Groundwater Encountered: 1 78 ft. 2. 78 ft. 3. 78 ft.
WELL'S STATIC WATER LEVEL: 77.93 ft. below land surface measured on mo/day/yr 10-30-95
Pump test data: Well water was 78 ft. after 78 hours pumping 78 gpm
Est. Yield 78 gpm: Well water was 78 ft. after 78 hours pumping 78 gpm
Bore Hole Diameter: 8 1/4 in. to 95.5 ft. and 95.5 in. to 95.5 ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted No X
Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded Trilock
Blank casing diameter 2 in. to 62.7 ft. Dia 62.7 in. to 62.7 ft. Dia 62.7 in. to 62.7 ft. Dia 62.7 in. to 62.7 ft. Dia
Casing height above land surface 2 in. weight 62.7 lbs./ft. Wall thickness or gauge No. EXH 40

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 62.7 ft. to 88.13 ft. From 62.7 ft. to 88.13 ft. From 62.7 ft. to 88.13 ft. From 62.7 ft. to 88.13 ft.
GRAVEL PACK INTERVALS: From 61 ft. to 95.5 ft. From 61 ft. to 95.5 ft. From 61 ft. to 95.5 ft. From 61 ft. to 95.5 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0.5 ft. to 60 ft. From 0.5 ft. to 60 ft. From 0.5 ft. to 60 ft. From 0.5 ft. to 60 ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

Direction from well? East How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	<u>0.5</u>	<u>Concrete, fine sand</u>			
1.0	<u>8.0</u>	<u>Brown silty clay</u>			
8.0	<u>28</u>	<u>Reddish brown clayey silt</u>			
28	<u>95.5</u>	<u>Sand, fine to medium</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/11/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 529 This Water Well Record was completed on (mo/day/yr) 10-4-96 under the business name of Geotechnology Inc by (signature) HT Baker