

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: McPherson		SE ¼ SE ¼ NE ¼	29	T 19 S	R 3 EW
Distance and direction from nearest town or city street address of well if located within city? 115 W. Kansas, McPherson					
2 WATER WELL OWNER: Green Lantern					
RR#, St. Address, Box # : PO Box 856			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Salina, KS 67402			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 120 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft 2. ft 3. ft			
		WELL'S STATIC WATER LEVEL: 94.63 ft. below land surface measured on mo/day/yr 7/14/2014			
		Pump test data: Well water was NA ft. after hours pumping gpm			
		Est. Yield NA gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 in. to 122 ft. and in. to ft			
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring					
Was a chemical/bacteriological sample submitted to Department? Yes.....No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No <input checked="" type="checkbox"/>					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC		4 ABS	7 Fiberglass		Threaded. <input checked="" type="checkbox"/>
Blank casing diameter 4 in. to 90 ft. Dia. in. to ft. Dia. in. to ft.					
Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No. Sch. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 90 ft. to 120 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 85 ft. to 122 ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete					
Grout intervals: From 0 ft. to 2 ft. From 2 ft. to 85 ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
13 Insecticide storage					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	Concrete,			
0.5	5	Fill, clayey sand,			
5	24	Clay, Red Brown			
24	38	Clay, Orange Brown			
38	55	Clay, Lt. Brown			
55	75	Clay, Lt. Gray			
75	80	Silt, Gray Brown			
80	90	Clay, m sand and gravel, Tan to Gray			
90	95	Clay, sandy (m-f), Tan			
95	105	Sand, m-c, Brown			
105	110	Clay, Gray			
110	120	Sand, f-m, Brown			
					MW13, Flushmount
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/27/2014 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 7/16/14					
under the business name of GeoCore, Inc. by (signature) <i>[Signature]</i>					