

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: McPherson		NE ¼ NE ¼ SE ¼	29	T 19 S	R 3 E/W
Distance and direction from nearest town or city street address of well if located within city? 115 W. Kansas, McPherson					
2 WATER WELL OWNER: Green Lantern					
RR#, St. Address, Box # : PO Box 856			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Salina, KS 67402			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 120 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 95.24 ft. below land surface measured on mo/day/yr 7/14/2014			
		Pump test data: Well water was NA ft. after hours pumping gpm			
		Est. Yield NA gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 in. to 122 ft. and in. to ft.			
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes.....No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No <input checked="" type="checkbox"/>					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
			7 Fiberglass		Threaded. <input checked="" type="checkbox"/>
Blank casing diameter 4 in. to 90 ft. Dia. in. to ft. Dia. in. to ft.					
Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No. Sch. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL					
1 Steel		3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
SCREEN-PERFORATED INTERVALS: From 90 ft. to 120 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 84 ft. to 122 ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete					
Grout intervals: From 0 ft. to 2 ft. From 2 ft. to 84 ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Topsoil, organic matter, Black			
2	20	Silt, Dark Brown to Brown			
20	30	Clay, silty, Lt. Brown			
30	40	Silt, some clay, Lt. Brown			
40	45	Clay, Black			
45	80	Clay, silty, Lt. Gray Brown			
80	95	Clay, sandy, Lt. Brown to Gray Brown			
95	100	Sand, c, Tan			
100	105	Clay, sandy, Lt. Brown			
105	110	Sand, m, Tan			
110	115	Clay, Lt. Brown			
115	121	Clay, sandy, Lt. Brown			
121	122	Sand, c, Tan			MW10R, Flushmount
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/3/2014 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 7/16/14					
under the business name of GeoCore, Inc. by (signature) <i>Dan Bell</i>					