			WATER	R WELL RECORD	Form W	VC-5 KSA	82a-12					
	N OF WAT		Fraction	an.		Section Nun	nber		p Number	1	e Numb	$\sim$ 1
	cPherso	n from nearest town	SE 1/4		NW 1/4	29		Т	19 s	R	3	E(W)
		as, McPhers	•		ated within c	ity?			0194	8019	MW-	_2
		NER: Kerr-Mc			ion				0174		****	
_		# : P.O. Box		ing corporat	.1011			Board	of Agriculture, I	Division of M	Vator D	osourcos
		: Houston		7253					ation Number:	DIVISION OF V	valer m	BSOUICES
		CATION WITH 4			88.0		E)/ATIC			e Elev:	1489	9.01
AN "X" I	N SECTION	BOX:	epth(s) Ground	water Encountered	1 7.	5.6	.ft. 2		ft. 3			ft.
<b>₹</b>	!	w	ELL'S STATIC	WATER LEVEL	78,33	ft. below lane	d surfac	e measure	d on mo/day/yr	08/.23	/94.	
_	- NW	NE		test data: Well w								
[	- , <b>;;;</b> ;	Es		gpm: _Well w								
≝     ⊬   ⊢	i X		ore Hole Diame	ter 8 • 25 in.	to 8	8.0	.ft., and	<b>d</b>	in	. to		ft.
ŧ w ├	!	· · · · w	ELL WATER T	O BE USED AS:		water supply		Air conditio	•	Injection we	eli	
īL	_ sw	SE	1 Domestic	3 Feedlot		d water suppl				Other (Spec	•	, I
	- 311	i II	2 Irrigation	4 Industrial					well			
Į L			/as a chemical/t itted	pacteriological samp	ole submitted	to Departmer			X; If yes ected? Yes	, mo/day/yr No	-	was sub- X
5 TYPE O	F BLANK C	ASING USED:		5 Wrought iron	8 C	oncrete tile			JOINTS: Glue			
1 Ste		3 RMP (SR)		6 Asbestos-Ceme	ent 9 C	ther (specify	below)		Weld	ed		
(2)PV	С	4 ABS		7 Fiberglass						aded		
		in										
Casing heigh	ght above la	ınd surface <del>.</del> 3		.in., weight		<u>.</u>	lbs./ft.	Wall thickn	ess or gauge N	lo Sche	eduTe	.40
TYPE OF S	SCREEN O	R PERFORATION I	MATERIAL:		(	7 <b>)</b> PVC		10	Asbestos-ceme	ent		
1 Ste	el	3 Stainless s	teel	5 Fiberglass		RMP (SR)		11	Other (specify)			
2 Bra	ass	4 Galvanized	steel	6 Concrete tile		9 ABS		12	None used (or	en hole)		
SCREEN C	OR PERFOR	RATION OPENINGS		5 G	auzed wrapp	ed	8	8 Saw cut		11 None	(open h	ole)
1 Co	ntinuous slo			6 W	ire wrapped		ę	9 Drilled ho	oles			
2 Lou	uvered shutt	er 4 Key	punched		orch cut	00			pecify)			
SCREEN-F	PERFORATE	ED INTERVALS:	From	. 6.3 ft. to	0	88 ft.	., From		ft. 1	to		ft.
G	RAVEL PA	CK INTERVALS:		ft. to								
	ALIA CE LA	OK WITEHWALO.	From	ft. t			., From		ft.			ft.
6 GROUT	MATERIAL	: 1 Neat cer		2 Cement grout	<u>(3)</u>	Bentonite	4 Ot					
Grout Inter				ft., From	61	ft. to	63					
		ource of possible co					Livesto			Abandoned		
	ptic tank	4 Lateral		7 Pit privy			Fuel sto	•		Dil well/Gas		
2 Sewer lines 5 Cess po							•			6) Other (specify below)		
		er lines 6 Seepag					13 Insecticide storageUST					
Direction fr			,	,			w many	•				
FROM	TO		LITHOLOGIC	LOG	FRO				PLUGGING	INTERVALS	3	
0.0	0.4	Asphalt										
0.4	8.0			to Red-Bro	wn							
8.0	13.0		Clay, Very	Fine Sand;								
		Red-Brown										
13.0	38.0	Fine Sand W										
38.0	48.0	Fine to Med		With Silt								
		Seams; Tan										
48.0	88.0	Fine to Med	lium Sand	Tan to Whi	te							
7 CONTE	RACTOR'S	OR LANDOWNER'S	S CERTIFICAT	ION: This water we	ell was(1) c	onstructed (2	) recons	structed. or	(3) plugged un	der mv iuri	diction	and was
_		/year)	3/02/94						ne best of may ki			
		's License No		This Wate						1941	·	į
		me of Terrace	on Consul	tants, Inc.			(signatu		1to	is The	uli	سر
		pewriter or ball point pe			v. Please fill in				vers. Send ton three	copies to Kar	sas Dena	rtment
of Healt	th and Environn	nent, Bureau of Water, To	opeka, Kansas 666	20-0001. Telephone: 913-	296-5545. Send	one to WATER W	VELL OWN	NER and retain	one for your record	ds.	-,-	