WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | County | Fraction SW 1/4 SE 1/4 SW 1/4 | | Section number | | Township number | Ronge number | |
|---|--------------------------------------|-------------------------------|--|----------------|------|--|----------------------------------|---------------|
| 1. Location of well: | | | | | | T 19 s | R 34 | E N |
| Scott SW 1/4 SE 1/4 SW 1/4 S 2. Distance and direction from nearest town or city: 9W, 8S, 1 3/4W 3. Own | | | | | | Hattendorf Bro | | -62 |
| R.R. or | | | | | | Box 339 | | |
| Street address of well location if in city: Of Scott City, KS City, sto | | | | | ode: | Scott City, KS 67871 | | |
| 4. Locate with "X" in section below: Sketch map: | | | | | | 6. Bore hole dia in. Completion date Well depth | | |
| Septer | | | | | | 7 Cable tool X_ Rotary Driven Dug | | |
| | | | | | | Hollow rod Jetted Bored Reverse rotary | | |
| | | | | | | 8. Use: Domestic Public supply Industry | | |
| 3/4 m | | | | | | X Irrigation Air conditioning Stack Lawn Oil field water Other | | |
| SW SE | | | | | | 9. Casing: Material Plas. Height: Above r below | | |
| well Xwell | | | | | | Threaded Welded Gluesurface in. RMPX | | |
| S I Mile | | | | | | Dia. 5 in. to 155ft. dep | | |
| 5. Type and color of material | | | | From | То | Dia in. to ft. depth gage No. •250 | | |
| | | | | | | 10. Screen: Manufacturer's name Jess & Lowell | | |
| Clay | | | | 0 | 15 | Type RMP Dia. 5 in. | | |
| Gyp Rock H | | | | 15 | 18 | Length 40 ft. | | |
| | | | | | | ft. andft. | | |
| Clay | | | | 18 | 22 | Gravel pack? YES Size range of material $\frac{1}{2}$ -1/8 | | |
| Sdy clay T | | | | 22 | 35 | 11. Static water level: mo./day/yr. 115 ft. below land surface Date 6-28-75 | | |
| Fine sd clay | | | | 35 | 45 | 12. Pumping level below land surfaces: | | |
| | | | | | -4 | 144 ft. after 1 hrs. pumping 70 g.p.m. hrs. pumping g.p.m. | | |
| Sd rock | | | | 45 | 21 | Estimated maximum yield 70 g.p.m. | | |
| Fine sd clay | | | | | 62 | | | lay/yr. |
| Sd coarse | | | | | 121 | Yes X No 14. Well head completion: | Date | |
| | | | | 121 | | Pitless adapter Inches above grade | | |
| Sd rock | | | | | 123 | 1). Well grouted? | | . F |
| Sd coarse | | | | | 130 | Whith: Neat coment Bentonite Concr Depth: From ft. to ft. | | ncrefe - L |
| Fine sd clay | | | | 130 | 132 | 16. Nearest source of possible contamination: ft. 3960 Direction NE Type Septic | | |
| | | | | | 41.0 | ft. 3960 Direction — Well disinfected upon comple | | Na |
| Sd coarse | | | | | 140 | 17, Pump: | Not installed | = <u>\</u> "{ |
| Fine sd clay | | | | 140 | 150 | Manufacturer's name G Model number UTX 5043 | oulds | 440 P |
| Shale | | | | 150 | 155 | Length of drop pipe 149 | ± HP5 Volts' ft. capacity 20g | |
| | | | | | | Туре: | | |
| | | | | - | | X Submersible | Turbine Reciproce | ating 5 |
| (Use a second sheet if needed) | | | | | | Centrifugal | Other | 12. |
| 18. Elevation: | 19. Remarks: | | | | | 20. Water well contractor's This well was drilled under m | | , k |
| | | | | | | is true to the best of my know | | |
| Topography: | | | | | | Weishaar Dri | 11ing 2 | 32 \$ |
| Hill Slope. | | | | | | Business name | KS 67871 | se No. |
| Upland | | | | | | Significant Signif | wan so | — l-i |
| Valley | | | | | | Authorized rep | | |
| Forward the white, blo | ue and pink copies to the Department | of Health and Environment | | | | / | Form WWC | ~ 3 |